



US007324166B1

(12) **United States Patent**
Joslin et al.

(10) **Patent No.:** **US 7,324,166 B1**
(45) **Date of Patent:** **Jan. 29, 2008**

(54) **LIVE ACTOR INTEGRATION IN
PRE-RECORDED WELL KNOWN VIDEO**

(75) Inventors: **Robert W. Joslin**, Burbank, CA (US);
Christopher G. Brown, Sherman Oaks,
CA (US)

(73) Assignee: **Contour Entertainment Inc.**, Van
Nuys, CA (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 598 days.

(21) Appl. No.: **10/990,161**

(22) Filed: **Nov. 15, 2004**

5,227,863	A *	7/1993	Bilbrey et al.	348/578
5,249,039	A	9/1993	Chaplin	
5,305,107	A	4/1994	Gale et al.	
5,345,313	A *	9/1994	Blank	348/598
5,400,081	A *	3/1995	Chaplin	348/587
5,517,236	A	5/1996	Sergeant et al.	
5,737,031	A *	4/1998	Tzidon et al.	348/587
5,838,310	A *	11/1998	Uya	345/536
5,848,146	A	12/1998	Slattery	
5,852,438	A *	12/1998	Tomizawa et al.	715/738
5,872,565	A *	2/1999	Greaves et al.	715/723
5,886,747	A *	3/1999	Tzidon et al.	348/587
5,986,717	A *	11/1999	Fairhurst	348/584
5,986,718	A *	11/1999	Barwacz et al.	348/592
6,141,063	A *	10/2000	Gehrmann	348/592
6,144,366	A *	11/2000	Numazaki et al.	345/156
6,154,600	A *	11/2000	Newman et al.	386/4
6,204,840	B1 *	3/2001	Petelycky et al.	715/500.1

Related U.S. Application Data

(60) Provisional application No. 60/519,922, filed on Nov.
14, 2003.

(51) **Int. Cl.**
H04N 9/74 (2006.01)
H04N 9/75 (2006.01)
H04N 9/76 (2006.01)

(52) **U.S. Cl.** **348/722; 348/578; 348/584;**
348/586; 348/587; 715/723

(58) **Field of Classification Search** **348/722,**
348/578, 584, 586, 587, 589, 598, 600, 705,
348/14.11, 14.09, 153, 159; 382/284, 282,
382/283, 305; 715/723, 719

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,095,139	A	6/1978	Symonds et al.
4,688,105	A	8/1987	Block et al.
5,093,720	A	3/1992	Krause et al.
5,099,337	A	3/1992	Cury
5,175,618	A	12/1992	Ueda et al.


(Continued)

Primary Examiner—David Ometz
Assistant Examiner—Jean W. Désir
(74) *Attorney, Agent, or Firm*—Robert W. J. Usher

(57) **ABSTRACT**

The apparatus inserts a participant realistically into familiar background media to provide similar results to a completely original movie with multi-camera studio production and editing. An automated and simplified studio has multiple cameras and traditional studio devices such as teleprompters and controlled lighting presented to the consumer as an entertainment product. Previously produced, familiar media are modified to create the background video source and synchronous audio track. The participant is inserted via chroma key and the multiple cameras are used to create traditional establishing shots intercut with close-ups. These are controlled through a video switcher to create a real-time, finished recording that is stored on a digital server for later playback.

7 Claims, 9 Drawing Sheets



U.S. PATENT DOCUMENTS

6,266,100 B1 *	7/2001	Gloudemans et al.	348/587	6,909,438 B1 *	6/2005	White et al.	345/629
6,278,448 B1 *	8/2001	Brown et al.	715/866	6,919,892 B1 *	7/2005	Cheiky et al.	345/473
6,301,382 B1 *	10/2001	Smith et al.	382/162	7,024,677 B1 *	4/2006	Snyder et al.	725/86
6,320,624 B1 *	11/2001	Ayer et al.	348/584	7,034,886 B2 *	4/2006	Ross et al.	348/445
6,351,765 B1 *	2/2002	Pietropaolo et al.	709/218	7,038,699 B2 *	5/2006	Sato et al.	345/633
6,353,461 B1 *	3/2002	Shore et al.	348/722	7,071,953 B2 *	7/2006	Matsuoka et al.	345/629
6,452,612 B1 *	9/2002	Holtz et al.	715/723	7,091,993 B1 *	8/2006	Ahmad	345/629
6,454,415 B1 *	9/2002	Vlahos	353/30	7,095,450 B1 *	8/2006	Holmes et al.	348/586
6,456,300 B1 *	9/2002	Pettigrew	345/634	7,143,434 B1 *	11/2006	Paek et al.	725/142
6,460,018 B1 *	10/2002	Kasai et al.	705/8	7,164,441 B1 *	1/2007	Miyazaki et al.	348/239
6,476,874 B1	11/2002	Ito et al.		7,164,490 B2 *	1/2007	Manico et al.	358/1.18
6,538,396 B1 *	3/2003	Vlahos et al.	315/292	7,209,181 B2 *	4/2007	Kriegman	348/586
6,674,485 B2 *	1/2004	Akiyama et al.	348/586	7,230,653 B1 *	6/2007	Overton et al.	348/584
6,731,825 B1 *	5/2004	Acampora et al.	382/284	7,236,210 B2 *	6/2007	Iwase	348/584
6,753,929 B1 *	6/2004	Sheraizin et al.	348/586				

* cited by examiner




FIG. 1A




FIG. 1B




FIG. 2




FIG. 3



FIG. 4



Fig. 5



FIG. 6

ID#	Description	Quantity	Manufacturer	Model #
1 & 5	Video Camera, 1/2" CCD w/RGB	2	JVC	TK1270U
3 & 7	Pan/Tilt Unit	2	Philips	TC6270PT
2 & 6	8-48mm Motorized Zoom Lens	2	Computar	H6Z0812MP
4 & 8	Reciever Driver Unit	2	Philips	LTC8561
9	Tally Lights	5	Y Lighting	Model 88
10	41 space rack, 70 in.w/rear door	1	Middle Atlantic	MAA-ERK-4026
11	Interated Media Server	1	Granite Precision Inc.	Cont-02
12 & 13	RGB to Serial Converter w/Framesync	2	AJA Video	R20AD-F
14	Production Switcher	1	Ross Video	S1-007
14	Keyer/switcher serial interface port	1	Ross Video	S100-0060
15 & 16	LCD Monitor 15" (teleprompter)	2	Innovision	Mag 565
17	LCD Monitor 15" (OCC)	1	Innovision	Mag 565
18	PS-2 Keyboard	1	Mitsumi	KFKEA4XT
19	PS-2 Optical Mouse	1	Mitsumi	ECM-S6102
20	Dot Matix Receipt Printer (SP200 series)	1	Star Micronics	sp2216d42-120
21	Cash Drawer	1	APG	S186-6a-CW1816
22 & 23	Miniature Lavalier Microphone & PS	2	audio-technica	Pro7a
24	Audio Processor	1	Peavey	Digitool MX
25	Ross Component Monitoring Amp.	1	Ross Video	CMA-8011A
26	Recording Server	1	Contour Entertainment Inc.	custom
27	KVM Switch	1	Gefen Inc.	KS-104
29	32" T.V. Monitor, Audience View	1	JVC	AV32320
30	19" T.V. Mon., Guest View	1	Magnavox	MT1905B
31	VHS Record Deck, Serially controlled	1	JVC	SR-365U
32	4" LCD Video Monitor Tape/DVD preview	1	Marshall	V-LCD4-Pro
33	"Quiet Please-Recording" Lightbox	1	Custom	custom
34	Lighting Dimmer	1	Leprecon	LD-360DMX
35	6" Fresnel	4	Altman	65Q
36	Nook Light	2	Altman	Q-Lite
37	Blue Screen (stretched on frame)	1	Bill Ferrell Co.	custom
38	Teleprompter Glass (18"X15")	2	Denglas Technologies Inc.	MLBS-30

FIG. 7

SIGNAL LEGEND

— S —	SERIAL CONTROL, RS-232 OR DMX-512
— V —	ANALOG VIDEO, NTSC, RGB OR VGA
— A —	AUDIO, LINE LEVEL
— SD —	SERIAL DIGITAL VIDEO
— DC —	DC LOW VOLTAGE CONTROL AND FEEDBACK
— SW —	INTERNAL DEVICE COMMUNICATIONS, SOFTWARE
— SL —	SHOW LIGHTING POWER




FIG. 8

1

LIVE ACTOR INTEGRATION IN PRE-RECORDED WELL KNOWN VIDEO

RELATED APPLICATIONS

This application claims priority from provisional application 60/519,922 filed Nov. 14, 2003, the disclosure of which is incorporated herein by reference

BACKGROUND OF THE INVENTION

Traditional editing for storytelling on film (and later video) created and perfected the style of inter-cutting shots of varying focal lengths and at varying angles to communicate the positional relation between characters in establishing shots and to provide increased intensity of performance by using close-ups. The ability to cut away from one perspective to another also allowed the use of different takes within the same production. These techniques have become so commonplace that they are inculcated and accepted by everyone with any media exposure whatsoever.

These techniques have also been used for many years in live productions with multiple cameras from the beginning of Television as Live Broadcast TV to today's news, awards, sports and talk shows.

Since the mid 1960's as the "Studio Tours" flourished in the Los Angeles area, "simulated" shows were created where participant could take the role of actors on sets with contemporary equipment and create short video scenes from famous shows. This type of "live" production has become a Theme Park staple over the years and many versions of custom media inserting guests into the previously produced segment have been created.

On a separate path, beginning more than 20 years ago, as MTV exploded onto the scene, the evolution of audio Karaoke to music video setups were taking the first steps of simplifying the production studio apparatus to bring some version of these expensive production techniques to a new market as a simplified production studio. These were all single camera set-ups and were not attempting to accomplish anything more than a superimposition of the guest over an interesting background while the music played. There was no intent of interacting with the background.

The next step in the evolution was to insert participants into a background entirely pre-produced specifically for the purpose of inserting a participant member of the public who could interact by answering questions or reading prompts to give them the appearance of appearing on a television show. In one example, this was showcased a decade ago at EPCOT center in Florida where guests could do a brief interview with Jay Leno. This setup was reprised at the Olympic Village in Atlanta in 1996 and has been resident at the NBC Experience in Rockefeller Plaza since 1999. There are other options in the later location and another example in "Studio 39" in San Francisco. However, in all of these installations, a single camera is used to place the participant into a background scene produced specifically and only for that purpose.

SUMMARY OF THE INVENTION

A unique aspect of the invention is the utilization of the techniques of multi-Camera production and editing in tandem with the automated studio to create a short, story-driven video where the participant portrays a character and is inserted into the video using the combination of establishing shots and close-ups. This allows a whole new version of such videos to be created.

2

In a specific embodiment of the invention, existing television and film media is re-edited to create the short background media. The existing media is modified to eliminate an actor or otherwise alter the background media, thus allowing insertion of the participant into a similar position in the establishing shots. The close ups of actors within the production are re-edited along with new backgrounds to compliment the establishing shots for use in new close-ups with the patron. A new script is created to work the participant's voice into the existing dialogue. This is similar to the studio production efforts that were made in various television commercials in the 1980's and in the film "Forrest Gump" in 1994.

The present invention comprises an entertainment product that utilizes multiple cameras with motion and zoom capabilities to create a digitally stored resulting performance wherein the guest appears as an actor in a short, story-driven video where the combination of wider, establishing shots which compose the participant with actors and other elements in the pre-existing background media are intercut with close-ups of the participant superimposed on appropriate backgrounds to match the backgrounds of the other actors in the pre-existing background media.

The participant position and alignment during the performance is led by "Tally" lights that indicate where the guest should be looking in order to properly align with the characters in the background media. The dialogue for the participant to speak is indicated on traditional teleprompters. These teleprompters also indicate when to speak the dialogue by transforming the text color at the desired time to speak the line along with other directions for the participant to follow to further improve the illusion of the participant interacting with the characters in the background media.

The resulting performance is displayed in real-time on one or more large monitors to be viewed by the surrounding audience and the participants queuing to take their turn performing. The surrounding audience can view both the participant and the monitor(s) whereon the performance is displayed. The performance may be re-played off of the digital storage device for viewing and/or subsequent recording to consumable recording media such as DVD. The digitally stored performance may also be modified and uploaded to a server for subsequent download by the participant via the Internet.

According to one aspect, the invention provides apparatus for creating a story driven video in which images of a live participant are inserted, real time, as an actor in a background video formed by a pre-existing, well known video/story adapted to receive images of the live participant comprising:

a digital library of background media of selectable pre-recorded, well known video media that has been adapted to receive the image of a live participant so as to appear an actor;

operator input means;

means for selecting a background media from the digital library and for playing the background media selected to provide a first signal source for video in response to operator input via the operator input means;

means providing a lighted monochrome background for performance of the live participant;

talent lights for the live participant and means for automatically illuminating the talent lights during the performance to approximate intensity and color temperature of the background media;

a first video camera and a second video camera generating, respectively; a second video signal and a third video

3

signal representing, respectively, images corresponding to different camera shots of a live performance of a participant, means for receiving the first signal of background media from the selection means and for selecting/switching between the second video signal and the third video signal and for providing a real time combination of a selected signal with the first video signal by a chromakey process, resulting in a fourth video signal of composition video;

means for selecting between the first video signal and the fourth video signal to create a fifth video signal of combined video;

and recording the fifth video signal as participant's performance video to a server hard drive as a single file for immediate and future playback and retrieval

Preferably, the background media includes audio and the media selection means provides a first signal source for audio, further comprising: means for capturing and recording in real time a voice/sound of the participant and for mixing and combining the real time recording of the voice/sound of the participant with the first signal of background audio to provide a second audio signal; means for disabling the participant's voice/sound by selectively switching between the first and second audio signals to provide a third audio signal of composition audio; and means for combining the fifth video signal and the third audio signal as participant's performance video.

It is also preferred that means are provided for moving respective video cameras to preselected positions, based on a next scene of background media, and based on a height of a participant received by operator input via the operator input means; and, means for changing a zoom, focus and iris of the video cameras to preset positions, based on the next scene of background media, and based on the height of the participant.

More specifically, the invention includes means for retrieving a participant's performance video and modifying format thereof to a consumer broadcast standard format and recording the modified performance video to one of video tape and Digital Video Disk for purchase; and, means for retrieving a participant's performance video and modifying the format and resolution to compressed digital video for internet video streaming, and uploading to a server for later download by the participant via the internet.

According to another aspect, the invention provides a method for creating a story driven video in which images of a live participant are inserted, real time, as an actor in a familiar background video/story comprising the steps of; providing a pre-existing, well known video story; adapting the video story to receive images of the live participant by selecting scenes from the video story, creating an alternative background to provide a place for insertion of another image by creating an image layer using a frame image of a selected scene as a template, creating an opaque area visually matching the background video scenes on a previously transparent background layer on the frame image template to obscure a selected part of the video image; and layering the opaque area with the original video frame to provide a back ground video; saving and inserting the frames into a remainder of the original video; preparing a synchronized script; providing the script to the participant and taking selected shots of the participant performing the script with a video camera and inserting the shots in respective selected frames of the back ground video to provide a participants performance video.

A series of different background media are made and stored for access on demand in a digital library.

4

This brief summary is provided so that the nature of the invention may be understood. In addition, a specific example of the invention is described in significantly more detail in the following Description of the Preferred Embodiment in conjunction with the accompanying drawings, which, together, form a complete description.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A and FIG. 1B, when combined, represent a schematic block diagram of one embodiment of the invention showing the main electronic and electrical "active" components and their relation to each other. Power to the components other than Show Controlled Lighting is not shown.

FIG. 2 is a plan view of the major components of one embodiment of the invention. The structures for this embodiment and the monochrome backdrop illumination have been removed for clarity. The enclosures for camera 1 and camera 2 are cut-away to expose these elements.

FIG. 3 is a right elevation view of the major components of one embodiment of the invention. The structures for this embodiment and the monochrome backdrop illumination have been removed for clarity. Also the participant's view television monitor is removed for clarity. The enclosures for camera 1 and camera 2 are cut-away to expose these elements.

FIG. 4 shows a frame of a representative scene of video as it appears in the original recognizable video and audio presentation.

FIG. 5 shows a frame of a representative scene of video as it appears after digital modification. The modification removes a character or other background elements to allow for the insertion of the participant(s) into a scene in the recognizable video and audio presentation.

FIG. 6 shows a frame of a representative scene of video as the participant appears inserted into the scene of recognizable video and audio presentation.

FIG. 7 shows a parts list of the components of the preferred embodiment, wherein product ID numbers correspond to those in FIGS. 1, 2 & 3.

FIG. 8 is a signal flow diagram.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENT

FIGS. 1A and 1B are schematic block diagrams showing the video, audio and control interconnections of active components of the invention.

A first camera 1 has associated with it a zoom lens 2, a pan-tilt unit 3 with receiver/driver 4, (with motion and zoom lens control such as that described in U.S. Pat. No. 5,517,236 issued May 14, 1996 to Sergeant et al.) and analog to digital (A to D) converter with frame sync 12. This camera generates a video composite signal and red, green and blue video signals of the participant's performance for input to the A to D Converter. This camera also takes a composite signal as reference as input to the frame sync module located in the A to D converter 12. This signal is from video decoder located in the integrated media server 11, (manufactured by Granite Precision, Pine Mountain, Calif.).

A second camera 5 has associated with it a zoom lens 6, a pan-tilt unit 7 with receiver/driver 8, and analog to digital (A to D) converter with frame sync 13. This camera generates a video composite signal and red, green and blue video signals of the participant's performance for input to the A to D converters 3. This camera also takes a composite signal as

5

reference as input to the frame sync module located in the A to D converter **13**. This signal is from video decoder located in the integrated media server **11**.

If more than two cameras angles are required in another embodiment of the invention, the arrangement of the components described for the first and second cameras would be repeated for subsequent cameras. This would enable additional angles of video capture of the participants performance.

The production switcher **14**, (manufactured by Ross Video, Toronto, Canada) receives the background video as a serial digital signal from the Integrated media server **11**. The background video signal is used as fill in a digital chroma key process, (such as those described in U.S. Pat. No. 5,249,039 issued Sep. 28, 1993 to Chaplin, and in U.S. Pat. No. 5,305,107 issued Apr. 19, 1994 to Gale et al.), where the monochrome background from the cameras **1**, **5** is replaced with this background image. The production switcher **14** switches the background signal to the output when only background video is desired. Alternatively, the production switcher **14** is able to switch to any one of the composite signals created by the chroma key process described above. In this embodiment, there are two composite signals to choose from. The first of these composite signals is the video signal from camera **1** as the foreground and the background video signal from the integrated media server **11**. The second of these composite signals is the video signal from camera **5** as the foreground and the background video signal from the integrated media server **11**. The production switcher **14** is also able to add other video effects to enhance the output video signal. These include, but are not limited to mattes, dissolves and fades. The production switcher **14** in this preferred embodiment is controlled via serial RS-232 control from the integrated media server **11**.

The serial digital output signal from the production switcher **14** is routed to a digital to analog converter (D to A) **25**. This device converts the signal back to an analog NTSC video signal, and also distributes the signal to other devices. The devices the analog signal is routed to include the audience view monitor **29**, the participant view monitor **30** and a video encoder/decoder located in the recording server **26**, (such as those described in U.S. Pat. No. 5,175,618 issued Dec. 29, 1992 to Ueda et al. and U.S. Pat. No. 5,093,720 issued Mar. 3, 1992 to Krause et al.). In this embodiment, the encoder in the recording server **26** encodes the analog NTSC video signal to MPEG 2 format and stores the performance as a video file in the performance media library of the recording server **26** hard drive for later use. There is a KVM switch that enables a keyboard **18**, mouse **19** and monitor **17** to be shared between the integrated media server **11** and the recording server **26**.

Audio for the participant's performance is captured using a wired lav ("lavalier") microphone **22** and power supply **23**. In this embodiment, there are two lav microphones **22** and two power supplies **23**. This enables multiple participants to perform simultaneously. An audio processor **24** combines the participants' voice audio signal with the background audio from the integrated media server **11** in the audio processor **24**. The audio processor **24** also performs other functions such as audio switching, equalization and delay, (with audio incorporation such as that described in U.S. Pat. No. 5,848,146 issued Dec. 8, 1998 to Slattery). The audio signal is routed from the audio processor **24**, to an audience view monitor **29**, a participant view monitor **30** and to the video encoder/decoder located in the recording server **26**. In this embodiment, the video encoder/decoder in the recording server **26** encodes the stereo audio and analog

6

NTSC video signal to MPEG 2 format and stores the performance as a video file in the performance media library of the recording server **26** for later use.

The recording server **26** can output the video and combined audio from a previously recorded performance. The video signal is decoded and distributed to a VHS recorder **31**. The performance video can be monitored by the operator during recording by viewing a preview monitor **32**. The recording server **26** communicates device control to the video recorder **31** via a Serial RS-232. The performance video can also be authored/edited and burned to a DVD automatically utilizing DVD authoring and burning software and hardware provided in the recording server **26** for such task.

The timing and automation of the devices to sync with the background media is all pre-programmed in the show control software of the integrated media server **11**. The participant is cued to speak lines and given directions for actions by two teleprompters **15**, **16** consisting of LCD screens viewed through semi-reflective glass in front of each camera **1** and **5**, respectively. Multiple tally lights **9** instruct the participant where to look during the performance to align properly with characters and elements in the background media. The timing of these tally lights is communicated through Serial RS-232 from the integrated media server **11** to the pan/tilt receiver/driver units **4**, **8**. The tally lights **9** are auxiliary outputs of the receiver/driver units **4**, **8**. An additional auxiliary output of receiver/driver unit **4** lights the "Quiet Please, Recording" light box **33**.

Four talent lights **35** are automated during the performance to match, approximately, the lighting on the foreground participant with lighting in the original background media. The lights are cued by the integrated media server **11** which communicates via DMX **512** to the lighting dimmer **34**, (such as that described in U.S. Pat. No. 4,095,139 issued Jun. 13, 1978 to Symounds et al.)

The selection of the background media, and its associated device control, is initiated by an operator. The operator communicates to the integrated media server **11** using the (conventional) computer keyboard **18**, mouse **19** and monitor **17**. The process is automated with operator prompts on monitor **17**. The point of sale functions for VHS tape and DVD sales are also automated by the recording server **26** which communicates serially with, and controls, a receipt printer **20** and cash drawer **21**, via a RS-232.

In FIG. 2, a participant is shown in the approximate performance position, situated in front of an illuminated monochrome screen **37**. The participant is illuminated by talent lights **35**, **36**. The tally lights **9** are distributed around the perimeter right side and bottom.

The lav microphone **22** and power supply **23** for the performance audio are attached to the participant. The signal cable is routed to other audio components housed in the electronics enclosure **10** as shown in FIGS. 1A and 1B.

The audience view monitor **29** is located on the lower left, and for display to an audience situated to the left in plan view. The participant view television monitor **30** is located directly in front of the participant.

The operator control and point of sale items located to the left of the main electronics enclosure **109** include the keyboard **18**, mouse **19**, monitor **17**, receipt printer **20** and cash drawer **21**. These route directly to the integrated media server **11**, not shown, which is located in electronic enclosure **10**.

Electronic enclosure **10** is cut away to show the video camera **1**, zoom lens **2**, pan/tilt unit **3**, the teleprompter monitor **15** the teleprompter glass **38** and one of the tally

7

lights 9. Other components located in electronic enclosure 10 but not shown in this view include: pan/tilt receiver-driver 4, video A to D converters 12, 13, production switcher 14, integrated media server 11, audio processor 24, video D to A converter 25, recording server 26, VHS recorder 31, and lighting dimmer 34.

Electronic enclosure 39 is cut away to show the video camera 5, zoom lens 6, pan/tilt unit 7, the teleprompter monitor 16 the teleprompter glass 38 and one of the tally lights 9. Other components located in electronic enclosure 39 but not shown in this view include the pan/tilt receiver-driver 8.

In FIG. 3, a participant is shown in the approximate performance position, situated in front of an illuminated monochrome screen 37. The participant is illuminated by talent lights 35, 36. Tally lights 9 are distributed at approximate eye level.

The lav microphone 22 and power supply 23 for the performance audio is shown attached to the participant. The cabling for this device is not shown, but is routed to other audio components in the electronics enclosure 10, as indicated in FIGS. 1A and 1B.

The audience view monitor 29 is located on the upper left behind the electronic enclosure 10. The participant view television monitor 30 has been omitted to better show other items in the electronic enclosure 10.

The operator control and point of sale items are not shown in this view but are located behind the main electronics enclosure 10. These include the keyboard 18, mouse 19, monitor 17, receipt printer 20 and cash drawer 21.

Electronic enclosure 10 is cut away to show the video camera 1, zoom lens 2, pan/tilt unit 3, the teleprompter monitor 15 the teleprompter glass 42 and one of the tally lights 9. Other components located in electronic enclosure 10 but not shown in this view include: pan/tilt receiver-driver 4, video A to D converters 12, 13, production switcher 14, integrated media server 11, audio processor 24, video D to A converter 25, recording server 26, VHS recorder 31, and the lighting dimmer 34.

Electronic enclosure 39 is cut away to show the video camera 5, zoom lens 6, pan/tilt unit 7, the teleprompter monitor 16 the teleprompter glass 38 and one of the tally lights 9. Also shown here is the pan/tilt receiver-driver 8 attached to the structure for electronic enclosure 39.

A description of the methods used to create the background media follows:

Recognizable, well-known media such as a movie or television show is converted to video format (if not already in that format). With the final integration of a participant actor in mind, the video is edited to a shorter, story-driven series of video segments using a computer-based video editing system such as Final Cut Pro from Apple Computer, Inc. or the Avid editing system from Avid Technology, Inc. The result is media prepared for incorporation of video and audio of the participant and a position is made for the insertion by the chromakey process.

Once the video is edited, the scenes in which the participant will perform are selected and a representative frame of video from each scene is captured and converted and exported as an image format such as JPEG. This process is accomplished using the editing software described above. One image per scene is selected to act as a template for the next step. FIG. 4 is a representation of this step of the method.

Each image selected is then altered using a photo editing system such as Photoshop from Adobe Systems, Inc. In the alteration process an alternate background is created to

8

provide a place for the future insertion of the (image of) the participant actor by the system devices of the invention described previously. In the photo editing software a image layer is created using the original video frame image as a template. An opaque area is created on a normally transparent background layer to cover over part of the video image. This opaque area is artistically edited to match the video colors, quality and character. When layered with the original video frame, a place is created for the future integration of the participant actor as represented in FIG. 5. Note that several of these frames can be made for use in the video editing system if animation of the background is desired.

These images are then saved in an appropriate resolution (720x480 in this embodiment) as an image file, such as JPEG to be imported to the video editing system. Once the frames are imported, they are then inserted into the video timeline at the appropriate position as a layer of video on top of the original video sequence. This results in a video sequence ready for integration of the participant actor as in FIG. 5.

The audio is then edited to accommodate the participant actor's spoken lines and, optionally, audio sweetening, music or other audio manipulations are performed in a studio or with other audio editing software, to create audio that is similar in character, volume and background score to the original yet still allow for incorporation of the participant actor's voice.

On completion of the video and audio, the entire sequence is then exported/converted in a compressed video format such as MPEG2. This background media file is then incorporated into the video background media library of the integrated media server 11 for later use. The system then integrates the participant actor with the background in the appropriate locations, as represented by FIG. 6.

A description of the signal flow follows, with reference to FIG. 8.

Operator input to show control software in the integrated media server 11 first sets variables that automate the devices in the system. The variables that are initially set are; the episode that will be displayed (background media and show control sequence), the height of the individual (chosen from five height ranges) and the name of the participant (for use in identifying the individuals file later in the recording server 26).

Setting the episode variable causes the show control software to initiate the video sequence by directing the video decoder to locate and buffer the appropriate video file from the background media library. Once buffered, the video file is started by the show control software. Further, the episode variable setting selects in the show control software the show sequence that will be run. On setting this variable the show control software initiates control of the devices of the system, and sets them to their initial position settings through the serial control interface (RS-232) and the DMX-512 control interface. The devices that are initialized are the production switcher 14, the camera control units 4 & 8, the audio processor 24 and the lighting dimmer 34.

The participant's height variable further modifies the show control software setting select commands sent to the camera control modules once the show is started, to select from a different set of presets in the camera control units 4 & 8 which conform to the height range of the participant and a particular scene of the background media file.

The variable for the name of the participant is used by the show control software to initialize the recording server 26 from the serial control interface of the integrated media server 11 and to the recording server 26. Furthermore, the

software provides packet information used by the recording server **26** to name the video file that will be created, (which name is derived from the participant initials, the time and the date of the performance). In this process, the recording server **26** communicates internally using the encoding/recording software to the video encoder/decoder to encode an incoming signal to a compressed video file (MPEG-2), and to save this file in a specified folder in the performance media library. Also the encoding/recording software communicates a time in seconds that the video encoder/decoder will encode the video stream. The actual encoding process starts once the show sequence is started. This is a command from the integrated media server **11** via the same serial control interfaces mentioned earlier.

Operator input to the integrated media server **11** causes it to start the selected show sequence. The show control software commands the video decoder to start the pre-selected video sequence. On show sequence start, the system devices change, if necessary, to accommodate the height of the individual for the first scene. The changes are communicated from the integrated media server **11** to the camera control units **4** & **8**. Also on start, the integrated media server **11** communicates to the recording server **26** to start the encoding process referred to earlier.

Once the show has started the integrated media server **11** updates and changes the communications to the system devices based on show control software settings in the integrated media server **11** and based on presets in the system devices. The system devices that are continuously controlled during the performance are the production switcher **14**, the camera control units **4** & **8**, the audio processor **24** and the lighting dimmer **34**. All the communications are from the serial interface of the integrated media server **11** to the serial input of the device except the lighting dimmer **34**. The lighting dimmer **34** receives a signal from the DMX-512 control interface of the integrated media server.

While the show sequence is running the show control software sends teleprompter text to the computer display of the integrated media server **11**. The computer display interface (video graphic card) is set to two monitors side by side at 1120x768 resolution. One of the two monitors is used as the operators GUI of the integrated media server **11**, while the other monitor receives the teleprompter text that is displayed in a backwards font. This backward text signal is split and sent to two LCD monitors that are viewed reflected from a partially reflective glass surface. These are the teleprompters **15** & **16**. The show control software in the integrated media server **11** displays the teleprompter text in "white" and the changes the color to "green" at the appropriate moment for the participant to speak the dialog. Acting instructions are displayed in "red".

The cameras **1** & **5** signals are analog RGB signals routed to analog to digital (A to D) converters **12** & **13**. These A to D converters have a frame sync module to allow the cameras to sync to a remote sync signal based on the "green" signal of the respective camera. For clarity the sync signals are not shown in FIG. **8**. The A to D converters **12** & **13** convert the signal to serial digital video which are routed to the production switcher **14**.

The production switcher **14** receives serial digital video signals from the integrated media server **11** (the background media) and from each of the cameras **1** & **5** (participant in front of a monochromatic background). The production switcher **14** processes the serial digital video signal in response to commands from the show control software of the integrated media server **11** via the serial control inter-

face. A typical command set will first set the production switcher to a set of preset functions such as chroma key, mask, dissolve, cut etc. Each of the functions can be in the on or off state (routed to the output of the production switcher, or not) depending on what is required for the show sequence. The next command will take any one or any number of these functions to the opposite state. For example the participant can be cut into the background (chroma key+cut) in a single frame of video, or dissolved-in (chroma key+dissolve) over a number of seconds. The next command might set up the next scene, and so on.

The audio processor **24** receives a background media audio signal from the video decoder on the integrated media server **11**. It also receives audio signals from one or more lav microphones and power supplies **22** & **23**. Show control software in the integrated media server **11** commands the audio processor **24**, via the serial control interface (RS-232), to presets during the show sequence. Each preset has internal settings for routing, equalization and delay. In this way the participants voice can be muted during non-dialog moments.

The lighting dimmer **34** receives DMX-512 serial signals during the show sequence. Unlike the other show system devices, the lighting dimmer **34** does not use presets, but instead changes the intensity of each light **35** independently, based on the DMX-512 protocol. The lights **35** are illuminated individually or in groups to illuminate the participant in a way that approximates the lighting of the background media and actors.

Immediately before ending the show sequence, the show control software in the integrated media server **11** communicates with all system devices and returns them to an initial setting.

When the show sequence has finished the recording, server **26** has a compressed video file (MPEG-2) of the participant's performance in the appropriate folder of the performance media library. The GUI interface of the encoding/recording software permits the operator to select the participant's performance video file, and record it to VHS tape or to burn it to a DVD.

If the participant chooses to have the performance recorded to VHS tape, the operator will select the file and select the "record to VHS" option in the GUI of the recording server **26** encoding/recording software. When this is selected the encoding/recording software communicates to the video encoder/decoder to decode a video file and directs it to the specified location in the performance media library of the participant's performance video file. Further it communicates a time in seconds to continue the video decoding process. Simultaneously, the encoding/recording software in the recording server **26** communicates to the VHS recorder **31** through the serial control interface (RS-232). The VHS recorder **31** is initialized and is queried if a VHS tape is installed. If not the encoding/recording software in the recording server **26** will recognize this, and instruct the operator to install a tape. Once the tape is installed the operator can start the recording sequence using the GUI of the encoding/recording software of the recording server **26** to command the VHS recorder **31** to start recording while it commands the video encoder/decoder of the recording server **26** to decode the selected video. Once the video has been recorded the encoder/recorder software commands the video encoder/decoder to stop decoding the video file. It further commands the VHS recorder **31** to stop recording and to eject the tape.

If the participant chooses to have the performance on a DVD, the operator will select the file and select the "burn to DVD" option in the GUI of the recording server **26** encod-

11

ing/recording software. When this is selected the encoding/recording software communicates to the DVD authoring & burning software in the recording server 26, to author a video file and directs it to the specified location in the performance media library of the participant's performance video file. The DVD authoring and burning software will author the compressed video file to DVD compatible files, as well as add a main menu and appropriate images (from the DVD authoring & burning software). The DVD authoring & burning software will then communicate with the DVD burner in the recording server 26 to burn the DVD. The encoding/recording software continuously gets progress status from the DVD authoring & burning software and displays this on the GUI. Once the DVD burning process is complete the DVD disk is ejected and the encoding/recording software returns to a state ready for the next participants video file to be recorded to VHS tape or burned to DVD.

A brief synopsis of the participant's experience follows:

When the participant agrees to perform, the operator first obtains information from the participant including name, height, episode (background media) in which to star, and possibly e-mail address. From this information the participant is instructed where to stand by the operator and where to look during the performance. This instruction includes which tally lights will be operational and when to look at them. It also includes information coming to the participant from the teleprompters such as lines, when to say them, and timely acting instructions.

Once the participant is ready the performance begins and the process is automated. The lines on the teleprompter appear in sync with the background media. The tally lights illuminate to cue the participant where to look at the appropriate time. The camera position, as well as zoom and focus are adjusted automatically to match the scene of background media and the height of the participant. In addition talent lights are illuminated at the appropriate time to approximate the lighting on the participant to that of the background media.

While the participant is performing, the production switcher automatically switches, at pre-determined intervals, between the background only scene signal and that of the composite scene of first camera plus background or the second camera plus background. More cameras can be used if required, resulting in additional video signals from which to choose.

During performance, the video signal output of the performance is being encoded to a digital computer file by the video encoder/decoder in the recording server. This digital file is cataloged and stored as an MPEG2 video file on an internal hard drive of the recording server.

On finishing the live performance, the participant is invited by the operator to purchase a video copy of the performance as a VHS tape, or a DVD with a choice of NTSC, PAL, SECAM or other consumer broadcast standard format. Once the selection is made, the integrated media server automates the task of decoding the digital video file and recording this to VHS tape, if chosen. If the participant chooses a DVD the integrated media server authors the digital video file to record to DVD, and then records the DVD via an internal DVD recording drive.

The participant may further choose to have the digital video file uploaded to a server for later retrieval via the internet for which the operator selects a function in the integrated media server to create a lower resolution version of the file, transfers the file to another computer via hard drive, disk or TCPIP, from any of which the file is later uploaded to a server for later retrieval.

12

All of the automated tasks are controlled by the integrated media server at pre-determined intervals that match that of the action in the background media, the height of the participant and the selection made concerning purchase of the video. These controls are in the form of Serial RS232 controls to (and from) the production switcher, the camera receiver/drivers, the VHS recorder and the receipt printer and cash drawer. All of these devices are controlled via RS232 protocols provided by the manufacturers of the devices. Controls for the talent lights and the audio router are in the form of digital I/O or DMX512.

The software controlling the integrated media server is customized to control the components of the participatory entertainment product.

The invention claimed is:

1. Apparatus for creating a story driven video in which images of a live participant are inserted, real time, as an actor in a background video formed by a pre-existing, well known video/story adapted to receive images of the live participant comprising:

a digital library of background media of selectable pre-recorded, well known video media that has been adapted to receive the image of a live participant so as to appear an actor;

operator input means;

means for selecting a background media from the digital library and for playing the background media selected to provide a first signal source for video in response to operator input via the operator input means;

means providing a lighted monochrome background for performance of the live participant;

talent lights for the live participant and means for automatically illuminating the talent lights during the performance to approximate intensity and color temperature of the background media;

a first video camera and a second video camera generating, respectively; a second video signal and a third video signal representing, respectively, images corresponding to different camera shots of a live performance of a participant,

means for receiving the first signal of background media from the selection means and for selecting/switching between the second video signal and the third video signal and for providing a real time combination of a selected signal with the first video signal by a chromakey process, resulting in a fourth video signal of composition video;

means for selecting between the first video signal and the fourth video signal to create a fifth video signal of combined video;

and recording the fifth video signal as participant's performance video to a server hard drive as a single file for immediate and future playback and retrieval.

2. Apparatus according to claim 1 wherein the background media includes audio and the media selection means provides a first signal source for audio, further comprising:

means for capturing and recording in real time a voice/sound of the participant and for mixing and combining the real time recording of the voice/sound of the participant with the first signal of background audio to provide a second audio signal;

means for disabling the participant's voice/sound by selectively switching between the first and second audio signals to provide a third audio signal of composition audio; and

means for combining the fifth video signal and the third audio signal as participant's performance video.

13

3. Apparatus according to claim 2 comprising;
 means for moving respective video cameras to preselected
 positions, based on a next scene of background media,
 and based on a height of a participant received by
 operator input via the operator input means;
 means for changing a zoom, focus and iris of the video
 cameras to preset positions, based on the next scene of
 background media, and based on the height of the
 participant.

4. Apparatus according to claim 3 comprising;
 means for retrieving a participant's performance video
 and modifying format thereof to a consumer broadcast
 standard format and recording the modified perfor-
 mance video to one of video tape and Digital Video
 Disk for purchase; and,
 means for retrieving a participant's performance video
 and modifying the format and resolution to compressed
 digital video for internet video streaming, and upload-
 ing to a server for later download by the participant via
 the internet.

5. A method for creating a story driven video in which
 images of a live participant are inserted, real time, as an
 actor in a familiar background video story comprising the
 steps of:
 providing a pre-existing, well known video story;
 adapting the video story to receive images of the live
 participant by selecting scenes from the video story,
 creating an alternative background to provide a place
 for insertion of another image by creating an image
 layer using a frame image of a selected scene as a
 template, creating an opaque area visually matching the
 background video scenes on a previously transparent
 background layer on the frame image template to
 obscure a selected part of the video image;
 and layering the opaque area with the original video frame
 to provide a back ground video;
 saving and inserting the frames into a remainder of the
 original video;
 preparing a synchronized script;
 providing the script to the participant and taking selected
 shots with at least one video camera of the participant
 performing the script with a video camera and inserting
 the shots in respective selected frames of the back-
 ground video to provide a participant's performance
 video.

14

6. A method according to claim 5 including the step of
 making a plurality of different background media and stor-
 ing the background media in a digital library.

7. Apparatus for creating a story driven video in which
 images of a live participant are inserted, real time, as an
 actor in a background video formed by a pre-existing, well
 known video/story adapted to receive images of the live
 participant comprising:

a digital library of background media of selectable pre-
 recorded, well known video media that has been
 adapted to receive the image of a live participant so as
 to appear an actor;

operator input means;

means for selecting a background media from the digital
 library and for playing the background media selected
 to provide a first signal source for video in response to
 operator input via the operator input means;

means providing a lighted monochrome background for
 performance of the live participant;

talent lights for the live participant and means for auto-
 matically illuminating the talent lights during the per-
 formance to approximate intensity and color tempera-
 ture of the background media;

a first video camera and a second video camera generat-
 ing, respectively; a second video signal and a third
 video signal representing, respectively, images corre-
 sponding to different camera shots of a live perfor-
 mance of a participant,

means for receiving the first signal of background media
 from the selection means and for selecting/switching
 between the second video signal and the third video
 signal and for providing a real time combination of a
 selected signal with the first video signal by a chro-
 makey process, resulting in a fourth video signal of
 composition video;

and recording the fourth video signal as participant's
 performance video to a server hard drive as a single file
 for immediate and future playback and retrieval.

* * * * *