



US009097957B2

(12) **United States Patent**
Pohlert et al.

(10) **Patent No.:** **US 9,097,957 B2**
(45) **Date of Patent:** **Aug. 4, 2015**

(54) **VERSATILE LIGHTING APPARATUS AND ASSOCIATED KIT**

(75) Inventors: **Rudy G. Pohlert**, Calabasas, CA (US);
Pat Grosswendt, Agoura, CA (US);
Kevin C. Baxter, Saugus, CA (US); **Ken S. Fisher**, Los Angeles, CA (US)

(73) Assignee: **Litepanels, LTD**, North Hollywood, CA (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **12/559,355**

(22) Filed: **Sep. 14, 2009**

(65) **Prior Publication Data**

US 2010/0002410 A1 Jan. 7, 2010

Related U.S. Application Data

(63) Continuation of application No. 11/005,564, filed on Dec. 4, 2004, now Pat. No. 7,604,361, which is a continuation-in-part of application No. 10/238,973, filed on Sep. 9, 2002, now Pat. No. 6,948,823, which is a continuation-in-part of application No. 09/949,206, filed on Sep. 7, 2001, now Pat. No. 6,749,310.

(51) **Int. Cl.**
F21S 9/02 (2006.01)
G03B 15/02 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **G03B 15/02** (2013.01); **G03B 15/05** (2013.01); **H04N 5/2256** (2013.01);
(Continued)

(58) **Field of Classification Search**
USPC 362/9, 3, 6, 8, 11, 16, 17, 18; 396/199, 396/431, 155, 182; 348/370, 371
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

1,991,814 A 2/1935 Mitchell 88/1
2,682,603 A 6/1954 Dine et al. 240/1.3

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2385646 3/2003 F21V 14/00
DE 200 08 703 U1 9/2000

(Continued)

OTHER PUBLICATIONS

Complaint in *Litepanels, Ltd and Litepanels, Inc. v. Dot Line Corp. and Infocus Camera & Imaging, LLC*, Case No. 6:2009cv00554, filed Dec. 10, 2009, in United States District Court, Eastern District of Texas, Tyler Division.

(Continued)

Primary Examiner — Jong-Suk (James) Lee


Assistant Examiner — Leah S Macchiarolo

(74) *Attorney, Agent, or Firm* — Irell & Manella LLP

(57) **ABSTRACT**

A lighting apparatus comprises a light panel having a panel frame, and a plurality of LEDs or other light elements secured to the panel frame. A self-contained battery unit securably attaches to the outside of the panel frame. The light panel may have a dimmer switch, and may also be capable of receiving power from a source other than the self-contained battery unit. The lighting apparatus can be mounted to a camera or a stand through adapters. Diffusion lenses or color gels can be integrated with or detachable from the light panel. The lighting apparatus may conveniently be provided in the form of a kit, with one or more of a light panel, self-contained battery unit, compact stand, connecting cable(s), adapter(s), lenses or color gels, and so on, provided in a single package.

23 Claims, 37 Drawing Sheets



- (51) **Int. Cl.**
- G03B 15/05** (2006.01)
- H04N 5/225** (2006.01)
- H05B 33/08** (2006.01)
- H05B 37/02** (2006.01)
- F21V 14/06** (2006.01)
- F21V 19/00** (2006.01)
- F21V 21/088** (2006.01)
- F21V 21/116** (2006.01)
- F21W 131/406** (2006.01)
- F21Y 101/02** (2006.01)
- F21Y 103/00** (2006.01)
- (52) **U.S. Cl.**
- CPC **H05B 33/086** (2013.01); **H05B 33/0863** (2013.01); **H05B 37/029** (2013.01); **F21S 9/02** (2013.01); **F21V 14/06** (2013.01); **F21V 19/001** (2013.01); **F21V 21/0885** (2013.01); **F21V 21/116** (2013.01); **F21W 2131/406** (2013.01); **F21Y 2101/02** (2013.01); **F21Y 2103/00** (2013.01); **G03B 2215/0539** (2013.01); **Y10S 362/80** (2013.01)
- (56) **References Cited**
- U.S. PATENT DOCUMENTS
- 3,794,828 A 2/1974 Arpino 240/4.2
- 3,827,071 A 7/1974 Turpin 95/1 R
- 4,019,042 A 4/1977 Baliozian 240/1.3
- 4,043,662 A 8/1977 Garfall 362/16
- 4,085,436 A 4/1978 Weiss 350/89
- 4,351,584 A 9/1982 Chandesais 354/63
- 4,469,418 A 9/1984 Stevens et al. 315/241
- 4,485,336 A 11/1984 Yoshiyama et al. 323/224
- 4,618,812 A 10/1986 Kawakami 396/544
- 4,687,312 A 8/1987 Navarro 362/33
- 4,729,070 A 3/1988 Chiu 354/413
- 4,777,566 A 10/1988 Lowell et al. 250/495.1
- 4,816,854 A 3/1989 Tsuji et al. 362/252
- 4,866,285 A 9/1989 Simms 358/93
- 4,893,223 A 1/1990 Arnold 348/371
- 4,931,866 A 6/1990 Charlesworth et al. 362/237
- 5,010,412 A * 4/1991 Garriss 362/306
- 5,038,258 A 8/1991 Koch et al. 362/9
- 5,083,253 A 1/1992 Hahnel 362/32
- 5,095,408 A 3/1992 Chen 396/544
- 5,143,436 A 9/1992 Baylor et al. 359/599
- 5,164,755 A 11/1992 King 362/9
- 5,187,611 A 2/1993 White et al. 362/9
- 5,213,404 A 5/1993 Chen 362/224
- 5,226,708 A 7/1993 Katahira et al. 29/4
- 5,235,497 A 8/1993 Costa 606/4
- 5,301,402 A 4/1994 Noel et al. 354/132
- 5,311,409 A 5/1994 King 362/3
- 5,312,393 A 5/1994 Mastel 348/131
- 5,345,284 A 9/1994 Tsuruta 352/131
- 5,440,385 A 8/1995 Fein et al. 354/76
- 5,450,291 A 9/1995 Kumagai 315/297
- 5,461,417 A 10/1995 White et al. 362/285
- 5,515,119 A 5/1996 Murdock et al. 362/10
- 5,539,485 A 7/1996 White 315/185 R
- 5,569,983 A 10/1996 McGuire et al. 396/429
- 5,580,163 A 12/1996 Johnson, II 262/89
- 5,588,732 A 12/1996 Sasaki et al. 348/131
- 5,598,068 A 1/1997 Shirai 362/244
- 5,604,550 A 2/1997 White 362/355
- 5,661,645 A 8/1997 Hochstein 438/301
- 5,684,530 A 11/1997 White 362/12
- 5,690,417 A 11/1997 Polidor et al. 315/159
- 5,713,661 A 2/1998 White 250/216
- 5,714,413 A 2/1998 Brigham et al. 362/216
- 5,739,639 A 4/1998 Johnson 362/33
- 5,758,942 A 6/1998 Fogal et al. 362/575
- 5,783,909 A 7/1998 Hochstein 315/291
- 5,808,295 A 9/1998 Takeda et al. 257/99
- 5,820,250 A 10/1998 Betts et al. 362/11
- 5,895,128 A 4/1999 Kishimoto et al. 362/236
- 5,897,195 A 4/1999 Choate 315/291
- 5,997,164 A 12/1999 Betts et al. 362/11
- 6,016,038 A 1/2000 Mueller et al. 362/216
- 6,022,124 A 2/2000 Bourn et al. 257/89
- 6,066,861 A 5/2000 Hohn et al. 362/216
- 6,095,661 A 8/2000 Lebens et al. 362/216
- 6,106,125 A 8/2000 Finn et al. 257/89
- 6,109,757 A 8/2000 Stephens 362/544
- 6,149,283 A 11/2000 Conway 362/574
- 6,150,774 A 11/2000 Mueller et al. 362/187
- 6,150,802 A 11/2000 Andrews 713/300
- 6,161,910 A 12/2000 Reisenauer et al. 362/184
- 6,166,496 A 12/2000 Lys et al. 315/185
- 6,211,626 B1 4/2001 Lys et al. 362/285
- 6,238,060 B1 5/2001 Bourn et al. 362/276
- 6,246,184 B1 6/2001 Salemo 362/246
- 6,252,254 B1 6/2001 Soules et al. 362/231
- 6,254,262 B1 7/2001 Crunk et al. 315/362
- 6,260,994 B1 7/2001 Matsumoto et al. 362/11
- 6,290,368 B1 9/2001 Lehrer 362/11
- 6,292,901 B1 9/2001 Lys et al. 362/11
- 6,305,818 B1 10/2001 Lebens et al. 362/11
- 6,320,330 B1 11/2001 Haavisto et al. 363/17
- 6,340,868 B1 1/2002 Lys et al. 315/216
- 6,357,893 B1 3/2002 Belliveau 340/815.4
- 6,390,647 B1 5/2002 Shaefer 362/11
- 6,454,437 B1 9/2002 Kelly 362/11
- 6,474,837 B1 11/2002 Belliveau 363/17
- 6,522,558 B2 2/2003 Henry 315/291
- 6,528,954 B1 3/2003 Lys et al. 313/46
- 6,554,452 B1 4/2003 Bourn et al. 327/108
- 6,556,067 B2 4/2003 Henry 362/247
- 6,577,080 B2 6/2003 Lys et al. 362/247
- 6,617,808 B2 9/2003 Ito et al. 362/247
- 6,719,434 B1 4/2004 Finn et al. 362/11
- 6,749,310 B2 6/2004 Pohlert et al. 362/11
- 6,791,283 B2 9/2004 Bowman et al. 315/291
- 6,806,659 B1 10/2004 Mueller et al. 315/295
- 6,824,283 B2 11/2004 Pohlert et al. 362/11
- 6,826,059 B2 11/2004 Bockle et al. 363/17
- 6,841,941 B2 1/2005 Kim et al. 315/216
- 6,864,641 B2 3/2005 Dygert 340/815.4
- 6,909,377 B2 6/2005 Eberl 362/11
- 6,948,823 B2 9/2005 Pohlert et al. 362/11
- 6,963,175 B2 11/2005 Archenhold et al. 315/291
- 6,982,518 B2 1/2006 Chou et al. 313/46
- 7,126,387 B2 10/2006 Nair 327/108
- 7,140,742 B2 11/2006 Pohlert et al. 362/11
- 7,152,996 B2 12/2006 Luk 362/11
- 7,163,302 B2 1/2007 Pohlert et al. 362/11
- 7,318,652 B2 1/2008 Pohlert et al. 362/11
- 7,331,681 B2 2/2008 Pohlert et al. 362/11
- 7,367,692 B2 5/2008 Maxik 315/291
- 7,429,117 B2 9/2008 Pohlert et al. 315/291
- 7,510,290 B2 3/2009 Pohlert et al. 362/11
- 7,604,361 B2 10/2009 Pohlert et al. 362/11
- 7,632,001 B2 12/2009 Hamada et al. 362/11
- 7,806,540 B2 10/2010 Yoneda 362/11
- 7,874,701 B2 1/2011 Pohlert et al. 362/11
- 7,972,022 B2 7/2011 Pohlert et al. 362/11
- 8,011,806 B2 9/2011 Shiraishi et al. 362/11
- 8,025,417 B2 9/2011 Pohlert et al. 362/11
- 2001/0010760 A1 8/2001 Saito 396/16
- 2002/0003602 A1 1/2002 Burckhardt 351/57
- 2002/0048169 A1 4/2002 Dowling et al. 362/234
- 2002/0048177 A1 4/2002 Rahm et al. 362/555
- 2002/0057061 A1 5/2002 Mueller et al. 315/291
- 2002/0084952 A1 7/2002 Morley et al. 345/32
- 2002/0110000 A1 8/2002 Marcus 362/555
- 2003/0160889 A1 8/2003 Angeli 348/362
- 2003/0180037 A1 9/2003 Sommers 396/155
- 2005/0040772 A1 2/2005 Guzman et al. 315/291
- 2005/0083704 A1 4/2005 Pohlert et al. 362/494
- 2005/0122705 A1 6/2005 Pohlert et al. 362/11
- 2005/0207196 A1 9/2005 Holmes et al. 363/126
- 2005/0225977 A1 10/2005 Amphlett 362/230

(56)

References Cited

U.S. PATENT DOCUMENTS

2005/0225980	A1	10/2005	Amphlett	362/244
2005/0231948	A1	10/2005	Pohlert et al.	362/237
2005/0243198	A1	11/2005	Pardikes	348/370
2005/0259409	A1	11/2005	Pohlert et al.	362/11
2006/0126319	A1	6/2006	Pohlert et al.	362/11

FOREIGN PATENT DOCUMENTS

DE	199 42 177	A1	3/2001	
DE	100313003	A1	1/2002	G05D 25/02
EP	1 072 884		1/2001	
EP	1 594 310	B1	11/2005	H04N 5/225
EP	1 291 708		8/2006	G03B 15/03
GB	2 087 592	A	5/1982	
GB	2 123 539	A *	2/1984	
GB	2 321 565	A	7/1998	
GB	2 369 730	A	6/2002	
GB	2 412 960	A	10/2005	G03B 15/02
GB	2 412 961	A	10/2005	G03B 15/03
JP	05-067553		3/1993	H01L 21/027
JP	05-089276		4/1993	G06K 7/10
JP	08-171803		7/1996	F21P 5/00
JP	09033445		2/1997	
JP	11-220177		8/1999	H01L 33/00
JP	2001-112715		4/2001	A61B 3/10
WO	WO 98/49872		11/1998	H05B 33/08
WO	WO 99/30537		6/1999	H05B 33/08
WO	WO 99/31560		6/1999	
WO	WO 99/57945		11/1999	H05B 37/00
WO	WO 99/36336		6/2000	F21K 7/00
WO	WO 02/01921		1/2002	H05B 33/08
WO	WO 03/023512	A2	3/2003	
WO	WO 03/023512	A3	3/2003	

OTHER PUBLICATIONS

U.S. Appl. No. 11/307,098, filed Jan. 23, 2006, Pohlert et al.

"Photographic Projects..Gene F. Rhodes..Feb. 6, 2002," website printout from www.photoprojects.net/ (Jan. 14, 2001).

"Special Lighting Nov. 13, 2001 . . . home," website printout from www.photoprojects.net/index8.html (Nov. 13, 2001).

"NERLITE Ring Illuminators," website printout from www.nerlite.com/products/ring.html (undated, printed out on Feb. 6, 2002).

NERLITE R-100 Series product information sheet (Jan. 30, 2002).

NERLITE R-70 plus Series Ring Illuminators product information sheet (Nov. 9, 2001).

NERLITE AR-100 Series Area Array Illuminators product information sheet (Nov. 15, 2001).

Edmund Industrial Optics, website printout from www.edmundoptics.com/IOD/DisplayProduct.cfm?productid=1538 (undated, printed out Feb. 6, 2002).

"Ringlichtsystem für Fotografie und Mikroskopie," website printout from www.dentic.de/lite/ledlite.htm (in German) (undated, printed out Feb. 7, 2002).

"Makroaufnahmen so leicht wie noch nie," website printout from www.digitalkamera.de/info/News/09/51-de.htm (in German) (Jul. 25, 2001).

"Imaging One bringt Makroblitz-Adapter für Nikon Coolpix 950/990," website printout from www.digitalkamera.de/info/news/08/22-de.htm (in German) (Apr. 9, 2001).

Nikon TTL Macro Speedlight SB-29 product sheet (undated).

"Luminaries" catalog excerpt, website printout from http://www.artisticlicence.com/cat1_1.htm (undated).

"Water-Fill WF 250 (WF250N)" brochure, Artistic License (UK) Ltd. (undated).

"Color-Fill Technology" press release, Artistic License (UK) Ltd. (undated).

"MultiMedia Quick Views," Color Kinetics Inc., 2002.

"Chromacore: in the beginning . . ." Color Kinetics Inc., 2002.

"Chromacore: under the hood," Color Kinetics Inc., 2002.

"Chromacore: the digital lighting fixture," Color Kinetics Inc., 2002.

"Chromacore: putting it all together," Color Kinetics Inc., 2002.

"Chromacore: a more colorful world," Color Kinetics Inc., 2002.

"Products: beauty, brains, and sensibility to boot!," website printout from <http://pro.colorkinetics.com/products/>, Color Kinetics Inc., 2002.

"ChromaRange," website printout from <http://www.pulsarlight.com/ChromaRange.htm>, Pulsar Light of Cambridge Ltd., 2000.

"White LED Clusters or Arrays, 12VDC Dimmers and 5mm LED Reflectors," website printout from <http://www.theledlight.com/led-assemblies.html>, AmericaWorks/The LED Light 1997-2000.

Millerson, Gerald, *Lighting for Television and Film*, Chapter 5, "Lighting people," pp. 96-139 (1991).

Millerson, Gerald, *Lighting for Television and Film*, Chapter 10, "Lighting equipment" pp. 295-350 (1991).

Carlson, Vern et al., *Professional Lighting Handbook*, pp. 15-40 (Focal Press, 1982).

"LED There Be Light," 4 pages, printed on Aug. 8, 2002.

"Kamio Ring Light," product brochure from www.kinoflo.com, printed on Aug. 9, 2002.

"LED There Be Light!" 5 pages (undated, printed out on Aug. 8, 2002).

TMB Featured Products, ProXS Professional Fixture Accessories from the Industry Leader, Aug. 8, 2002.

Cognex Machine Vision Illumination, printout from www.cognex.com/insight/In-Sight_Lighting.pdf, 2002 (printed out on Aug. 8, 2002).

In-Sight Machine Vision Sensor, dated Summer 2002.

Filmcrew, *The Art & Craft of Production*, Issue 27, 1999, cover page, pp. 4, 40.

"Spect-Light II, The LED Light by Concept," webpage printout from www.conceptlight.com/led.html, 2004, 2 pages.

Webpage printout from www.reflecmedia.com, 2002, printed on Oct. 26, 2005, 2 pages.

Webpage printout from www.bbc.co.uk/rd/projects/virtual/truematte/index.shtml, undated (printed on Oct. 26, 2005), 2 pages.

Grau, et al "Use of 3-D Techniques for Virtual Production," Invited paper presented at SPIE conference on "Videometrics and Optical Methods for 3D Shape Measurement", Jan. 22-23, 2001, San Jose, USA, 11 pages.

Kino Flo Fluorescent light photographs, unpublished.

Ringlite product, sold by Contrast Lighting Services, Inc. circa Sep. 21, 2001, described at www.fisherlight.com/level2/ringlite.html.

"LED Darkfield Ringlights suit industrial OEM applications," Archived news story dated Jan. 7, 2002, printed from <http://news.thomasnet.com/fullstory/5851> on Jul. 27, 2006.

"Intelligent LED Darkfield Ringlights from Schott-Fostec, LLC," Archived news story dated Jun. 5, 2001, printed from <http://news.thomasnet.com/fullstory/5851> on Jul. 27, 2006.

"LED there be light (Aug. 2003), A D.I.Y. Bright White LED Ringlight," dated Aug. 2003, printed from http://users.pandora.be/cisken/LED_ringlight/LED_ringlight.html on Jul. 27, 2006.

"LED Ringlight," dated May 20, 2001, printed from http://us.schott.com/fiberoptics/English/download/20.05.01ringlight_us.pdf on Jul. 27, 2006.

"ILP LED Ringlight" dated 2001, printed from <http://www.volpiusa.com/images/uploads/ILPLEDRinglight.pdf> on Jul. 27, 2006.

"Modern Classic SLRs Series: Additional info on Nikon Speedlights SB-1 to SB-21A/B," dated 1999, printed from <http://www.mir.com/rb/photography/hardwares/classics/nikonf3ver2/flash/sbltosb21/index7.htm> on Jul. 26, 2006.

Litepanels, LLC and Litepanels, Inc. v. Frezzolini Energy Systems Corp., Civil Action No. 2-06cv-143, filed Apr. 6, 2006.

Litepanels, LLC and Litepanels, Inc. v. VF Gadgets Inc. and Gekko Technology Ltd., Civil Action No. 2-06cv-167.

"The Video Battery Handbook," Anton/Bauer, Inc., Undated, pp. 1-64.

"Thermal Management Design of LED's," Nichia Application Note, Oct. 31, 2003, pp. 1-7.

"Cree XLamp LED Thermal Management," Cree LED Light, Cree, Inc., pp. 1-6.

Gekko Technology Ltd. Kisslite product information, printed from <http://web.archive.org/web/20040422044254/www.gekkotechnology.com/menu.html>, <http://web.archive.org/web/20040423041645/>

(56)

References Cited

OTHER PUBLICATIONS

www.geldcotechnology.com/products.html and http://web.archive.org/web/*/www.gekkotechnology.com, dated Apr. 19, 2004, 8 pages. App vi, Ex 6, "Aspect Ratio", www.schumachercamera.com, 1 page., 2005.

App viii, "CRIME-LITE® 4x4, LED ring light for forensic photography", www.fosterfreeman.co.uk, 1 page., Aug. 12, 2006.

Appx, "Philips Lumileds LUXEON® I 20mm range" www.carcloptics.com, 1 page, Nov. 21, 2006.

App xii, "Ringlite Resource Links", www.ringlite.com, 1 page, Sep. 12, 2006.

App xviii, Ex G, "Diopter Holder", American Cinematographer, www.theasc.com/magazine/feb99/PRODUCTS/index2.htm, Feb. 1999.

App xviii, Ex H, a-1, Untitled, No provenance, said to be production stills evidence of accessory bars that aren't supporting either the matte box or the follow focus but still in place for other devices, 12 pages, said to be: a) "Brown of Resolution", May 1933 b) "Madness of the Heart", 1948 c) "Outcast of the Islands", 1957 d) "Romanoff and Juliet" (supporting mattebox), 1959 e) "Lawrence of Arabia" (supporting matte box), 1960 f) "Lord Jim" (supporting Panavision Panazoom), 1964 g) "On Her Majesty's Secret Service" (supporting zoom lens, rangefinder sight and other gadgetry), 1969 h) "Performance" (Supporting zoom motor on Pavavision camera), 1970 i) "The Godfather 3" (Light and mattebox mounted on Panavision camera, 1989 j) Otto Heller BSC, died 1970 (with a light mounted on the camera with bracketry), 1970 or earlier k) "Courage Under Fire" (supporting zoom motor gears and operator's handle on Moviecam, 1996 l) "The Hurricane", 1999.

Clifford Coffin, Photographs from Vogue 1945 to 1955, ISBN: 15556706545, published by Stewart, Tabori & Chang 1997, p. 23 & 25.

Arri News Jun. 1997, p. 26.

Reflecmedia website printout, dated: Jan. 5, 2007, 2 pages.

Arri News Dec. 1997, p. 28, 1 page.

Arri News Jun. 1998, p. 30, 1 page.

www.bbc.co.uk/dr/awards/ibc1998-1.shtml webpage announcing 1998 IBC Awards, 1 page.

American Cinematographer magazine, pp. 63 and 66, Sep. 1991, vol. 72, No. 9, 4 pages.

Complaint in *Litepanels, LLC and Litepanels, Inc. v. Sony Electronics, Inc., Sony Corporation of America, Inc., and Sony corporation*, Civil Action No. 2:07-cv-508 (DF), filed Nov. 19, 2007 in United States District Court, Eastern District of Texas, Marshall Division. Patent Rule 4-3 Joint Claim Construction and Prehearing Statement, Sep. 19, 2007. 1) Table A: Claim Terms, Phrases, and Clauses Common to the '823 and '302 Patents, 2) Declaration of Professor Tracy Trotter, Sep. 19, 2007, 3) Expert Declaration of John Fagan, PhD in Support of Litepanels' Joint Claim Construction Statement, Sep. 19, 2007, 4) Exhibit "C" To Joint Claim Construction and Prehearing Statement.

Litepanels, LLC and Litepanels, Inc. Opening Claim Construction Brief [P.R. 4-5(a)] Regarding U.S. Patent Nos. '823, '310 and '302, Oct. 4, 2007, 1) Declaration of Joshua A. Burt in Support of Litepanels, LLC and Litepanels, Inc. Opening Claim Construction Brief, Oct. 4, 2007, A) Exhibit A: U.S. Patent 6,948,823, B) Exhibit B: U.S. Patent 6,749,310, C) Exhibit C: U.S. Patent 7,163,302, D) Exhibit D: U.S. Appl. No. 11/100,023, E) Exhibit E: Merriam-Webster Online Dictionary definition for "illuminate." Merriam-Webster Online Dictionary, Entry for Illuminate, <http://www.mw.com/dictionary/illuminate>, F) Exhibit F: Chart created to aid the Court in reviewing Litepanels' proposed claim construction, 2) Expert Declaration of John Fagan, PhD., in Support of Litepanels' Joint Claim Construction Statement, Oct. 3, 2007, A) Exhibit A: Curriculum Vitae of John E. Fagan, Ph.D., B) Exhibit B: The Wiley Electrical and Electronics Engineering Dictionary (2004), C) Exhibit C: PC Magazine's Encyclopedia (2007), 3) Expert Declaration of Professor Tracy Trotter, Oct. 3, 2007, A) Exhibit A: Curriculum Vitae of Tracy Trotter, B) Exhibit B: Hands-On Manual for Cinematographers; cover pages and p. 14.4.

Defendant Gekko Technology Ltd.'s Brief in Support of its Claim Construction [P.R. 4-5(a)], Oct. 15, 2007, A) Expert Declaration of David Amphlett in Support of Gekko Technology, Ltd.'s Brief in Support of Its Claim Construction, Oct. 15, 2007, 1) Curriculum Vitae of David Richard Amphlett, B) Declaration of William G. Shaw, Jr. In Support of Defendant Gekko Technology Ltd.'s Brief in Support of its Claim Construction [P.R. 4-5(a)], Oct. 15, 2007, 1) Exhibit B-1: an Amendment and Response to Office Action dated Oct. 31, 2003, taken from the prosecution history of the United States Patent and Trademark Office for U.S. Patent No. 6,749,310, 2) 2) Exhibit B-2: an Office Action Communication dated Jul. 7, 2003, taken from the prosecution history of the United States Patent and Trademark Office for U.S. Patent No. 6,749,310, 3) Exhibit B-3: the original claims of the patent applicant taken from the prosecution history of the United States Patent and Trademark Office for U.S. Patent No. 6,749,310.

Litepanels, LLC and Litepanels, Inc. Reply Claim Construction Brief Regarding U.S. Patent Nos. '823, '310 and '302, Oct. 25, 2007, A) Attachment a to Litepanels' Claim Construction Reply Brief, B) Declaration of Joshua A. Burt in Support of Litepanels, LLC and Litepanels, Inc. Reply Claim Construction Brief, Oct. 25, 2007, a) Exhibit A: Videotaped Deposition of David Richard Amphlett, Thursday, Oct. 18, 2007, b) Exhibit B: Videotaped Deposition of David Richard Amphlett, Wednesday, Oct. 24, 2007, c) Exhibit C: Definition for "fisheye" found in Merriam-Webster's Online Dictionary, <http://www.merriam-webster.com/dictionary/fisheye>, d) Exhibit D: Oct. 11, 2007 letter sent by Litepanels' counsel to Gekko's counsel proposing compromises pursuant to the Court's Oct. 2, 2007 Order, C) Supplemental Expert Declaration of Professor Tracy Trotter.

Memorandum Opinion, Dec. 6, 2007.

Defendant Gekko Technology Ltd. Renewed Disclosure of Invalidity Contentions, Aug. 2, 2007, Appendix "A" Contentions/Indefiniteness—Patent 310, Appendix "B" Contentions/Novelty—Patent 310, Appendix "C" Contentions/Obviousness—Patent 310, Appendix "D" Contentions/Indefiniteness—Patent 823, Appendix "E" Contentions/Novelty—Patent 823, Appendix "F" Contentions/Obviousness—Patent 823, Appendix "G" Contentions/Indefiniteness—Patent 302, Appendix "H" Contentions/Novelty—Patent 302, Appendix "I" Contentions/Obviousness—Patent 302.

Complaint in *SWIT Electronics Co., Ltd. v. Litepanels LLC*, Civil Action No. C07 02645 JCS, filed May 17, 2007 in United States District Court, Northern District of California.

Complaint in *Litepanels, LLC and Litepanels, Inc. v. Thomas McKay d/b/a Varizoom Lens Controls, and SWIT Electronics Co., Ltd.*, Civil Action No. 6:07-cv-239-LED, filed May 29, 2007 in United States District Court for the Eastern District of Texas.

Docket Sheet for *SWIT Electronics Co., Ltd v. Litepanels LLC*, Civil Action No. 6:07-cv-00480-LED [transferred case from C07 02645 JCS].

Transfer order for *SWIT Electronics Co., Ltd v. Litepanels LLC*, Civil Action No. C07 02645 JCS.

Camerapedia, Olympus Pen Cameras—Olympus Pen EE Series Camera Description and Photos ("The Pen EE Series"), found on the Internet at http://camerapedia.wikia.com/wiki/Olympus_Pen, undated.

Modern Classic SLRS Series, Olympus T-20 Flash, (c) 2000, found on the internet at <http://www.mir.com.my/rb/photography/hardwares/classics/olympusom1n2/shared/flash/t20.htm>, undated.

Olympus, OM-1 N (1979), Photo and Description of Olympus OM-1 MD Camera capability for detachable portable flash unit circa 1979, from website copyrighted by the Olympus Corporation, found on the internet at http://www.olympus-global.com/en/corc/history/camera/popup/om_om1n.html, undated.

CARID—Define Your Vehicle's True Identity, Spec-D(r)—Black LED Tail Lights, Taillight assembly from 2000 Cadillac Escalade, (c) CARID.com, found on the internet at <http://www.carid.com/2000-cadillac-escalade-taillights/spec-d-led-tail-lights-261194.html>, undated.

Digchips.com—Electronics Components Database, Luxeon Line DS21 Technical Data Sheet, Details on DS21 LED Lighting Array,

(56)

References Cited**OTHER PUBLICATIONS**

(c) 2005 Lumiled Lighting, found on the internet at <http://www.digchip.com/datasheets/parts/datasheets/parts/datasheets/989/DS21-pdf.php>, undated.

Lumiled Future Electronics—All in 1 Plug and Play Guide, Lumiled Product Catalog, by Future Electronics, Luxeon Flood (12 or 18 densely packed LEDs), dated Sep. 2004, found on the internet at http://www.produktinfo.conrad.com/datenblaetter/175000-199999/176290-in-01-en-Luxeon_LED_LXHL MB1D_blue.pdf.

Modern Classic SLRS Series—Additional Info on Nikon Speedlights SB-1, Discussion on DC power sources for Nikon Speedlights, (c) 1999, found on the internet at <http://www.mir.com.my/rb/photography/hardwares/classics/nikonf3ver2/flash/sb1tosb21/index2.htm#SB-2>, undated.

Kino Flo Lighting Systems, Kamio 6 lighting system, product detail depicts DC dimming capability, (c) Kino Flo Incorporated, found on the internet at <http://kinoflo.com/12VDC%020Systems/Kamio/Kamio.htm>, undated.

Tom Patrick McAuliffe, digitalcontentproducer.com—Film and Video Production in a Multi-Platform World, Shoot Review—Kino Flo Kamio 6—Ring Light System shines balanced, beautiful light, "... the 12VDC @ 6 amp power converter box and the dimmer box are built like metal tanks ...", dated Sep. 1, 2005, 12:00 PM, website copyrighted to NewBay Media, LLC, found on the internet at http://digitalcontentproducer.com/fieldprod/revfeat/video_kino_flo_kamio/.

Theledlight.com—Energy Efficient Green Technology, LED Application Notes—LED Basics, (C) Data Display Products Jan. 1, 2000, found on the internet at <http://www.theledlight.com/technical1.html>.

Ledtronics—Creating the Future of Light Since 1983, Tech Notes—LED Lens Configurations, Determining light illumination patterns from LEDs, website copyrighted by LEDTronics, Inc, website found on the internet at <http://www.ledtronics.com/TechNotes/TechNotes.aspx?id=19>, undated.

Request for Ex Parte Reexam, Proceeding No. 90/009,963, filed Oct. 26, 2011.

Linear Technology, LT1615/LT1615-1, Micropower Step-Up DC/DC Converters in SOT-23, pp. 1-8 (1998).

In the Matter of Certain LED Photographic Lighting Devices and Components Thereof, Investigation No. 337-TA-804, Notice of the Commission's Final Determination Finding A Violation of Section 337; Issuance of a General Exclusion Order; Termination of Certain Respondents Based on Consent Order; Issuance of Consent Order; and Termination of the Investigation dated Jan. 17, 2013.

In the Matter of Certain LED Photographic Lighting Devices and Components Thereof, Investigation No. 337-TA-804, Commission Opinion dated Feb. 28, 2013.

In the Matter of Certain LED Photographic Lighting Devices and Components Thereof, Investigation No. 337-TA- Litepanels, Ltd. and Litepanels, Inc. Verified Complaint Under Section 337 of the Tariff Act of 1930, as Amended filed against Proposed Respondents: Flolight, LLC, Prompter People, Inc., IKAN Corporation, Advanced Business Computer Services, LLC, Elation Lighting, Inc., Fotodiox Inc., Fuzhou F&V Photographic Equipment Co., Ltd. Yuyao Lishuai

Photo-Facility Co., Ltd., Yuyao Fotodiox Photo Equipment Co., Ltd., Shantou Nanguang Photographic Equipment Co., Ltd., Visio Light, Inc., Tianjin Wuqing Huanan Film and TV Equipment Factory, Stellar Lighting Systems, and Yuyao Lily Collection Co., Ltd., filed Aug. 3, 2011.

In the Matter of Certain LED Photographic Lighting Devices and Components Thereof, Investigation No. 337-TA-804, Response of Respondent Fotodiox, Inc. to Complaint and Notice of Investigation, dated Sep. 22, 2011.

In the Matter of Certain LED Photographic Lighting Devices and Components Thereof, Investigation No. 337-TA-804, Response of Respondent Elation Lighting Inc. to the Complaint of Litepanels Inc. and Litepanels LTD. Under Section 337 of the Tariff Act of 1930, as Amended, and Notice of Investigation, dated Sep. 22, 2011.

In the Matter of Certain LED Photographic Lighting Devices and Components Thereof, Investigation No. 337-TA-804, Response of Prompter People, Inc., Flolight, LLC, IKAN International Corporation, and Advanced Business Computer Services, LLC to the Verified Complaint of Litepanels, LTD and Litepanels, Inc. Under Section 337 of the Tariff Act of 1930, as Amended, dated Sep. 23, 2011.

"Schedules A, B and C, Invalidity Contentions" filed by Defendant Gekko Technology Ltd. on Dec. 19, 2006 in, *Litepanels, LLC and Litepanels, Inc. v. Vfgadgets Inc. and Gekko Technology Ltd.*, U.S. District Court, Eastern District of Texas, Marshall Division, Case No. 2:06 CV 167, 368 pages, Dec. 19, 2006.

1 page document, title unreadable, provenance unknown, said to be Play Catalogue date 1999, describing Holoset technology said to be developed by "Play" in cooperation with BBC, said to be available Fall 1999, said to be 1999.

3 page document entitled "Virtual Production", with BBC logo, said to be pp. 2, 3, 4, said to be May 1999.

1 page document, said to be BBC r&d annual review Apr. 1999-Mar. 2000, p. 18, said to be Mar. 2000.

BBC Research, Production Magic 2 pages, Dec. 20, 2006.

"viewercom" website, 2 pages, 2001.

Untitled, discusses photographing The Wiz, said to be "American Cinematographer Nov. 1978, pp. 1071, 1072, 1072", 3 pages, said to be Nov. 1978.

"LIGHTFLEX congratulate THE WIZ", said to be "American Cinematographer Nov. 1978, p. 1085", 1 page, said to be Nov. 1978.

"Lightflex: A Whole New World of Color on the Screen", Gerry Turpin, said to be "American Cinematographer Nov. 1978, pp. 1086, 1087", 2 pages, said to be Nov. 1978.




The NEW LIGHTFLEX a tool for Cinematography, said to be Eye-piece magazine Jan./Feb. 1986.

"Lumileds Releases Luxeon® K2 LEDs, Offering Industry-Leading Light Output, Thermal and Electrical Properties", press release for Luxeon® by Lumineds, 3 pages, Jan. 30, 2006.

Litepanels, Ltd and Litepanels, Inc. v. Switronix, Inc., Prompter People, Inc. d/b/a Q-Gear, Flolight, LLC and Omega Broadcast Group, L.P. Civil Action No. 6:09-Cv-1717 (LED), filed Oct. 14, 2013, ED Texas.

LED Fundamentals Thermal Characteristics of LEDs, OSRAM Opto Semiconductors, Aug. 16, 2011.

* cited by examiner






FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 11




FIG. 12




FIG. 13




FIG. 14

FIG. 15A






FIG. 15B

FIG. 15C






FIG. 16A







FIG. 16B






FIG. 17




FIG. 18




FIG. 19A




FIG. 19B




FIG. 20







FIG. 21








FIG. 25




FIG. 26






FIG. 27






FIG. 30A




FIG. 30B




FIG. 30C




FIG. 31




FIG. 32




FIG. 33





FIG. 34

*FIG. 35*




FIG. 36A




FIG. 37A




FIG. 36B




FIG. 37B




FIG. 36C




FIG. 37C




FIG. 37D





FIG. 37E

*FIG. 38A*




FIG. 38B




FIG. 39








FIG. 40






FIG. 42C




FIG. 42D




FIG. 43




FIG. 44




FIG. 45




FIG. 46




FIG. 47A




FIG. 47B




FIG. 48A




FIG. 48B




FIG. 49A




FIG. 49B





FIG. 50B

FIG. 51




FIG. 52C




FIG. 52A





FIG. 52B






FIG. 53A




FIG. 53B




FIG. 53C




FIG. 53D




FIG. 54





FIG. 55






FIG. 56




FIG. 57








FIG. 58






FIG. 63A




FIG. 63B

1

VERSATILE LIGHTING APPARATUS AND ASSOCIATED KIT

RELATED APPLICATION INFORMATION

This application is a continuation of U.S. patent application Ser. No. 11/005,564 filed on Dec. 4, 2004, which is a continuation-in-part of U.S. application Ser. No. 10/238,973 filed Sep. 9, 2002, now U.S. Pat. No. 6,948,823, which is a continuation-in-part of U.S. application Ser. No. 09/949,206 filed Sep. 7, 2001, now U.S. Pat. No. 6,749,310, hereby incorporated by reference as if set forth fully herein.

BACKGROUND OF THE INVENTION

1) Field of the Invention

The field of the present invention relates to lighting apparatus and systems as may be used in film, television, photography, and other applications.

2) Background

Lighting systems are an integral part of the film and photography industries. Proper illumination is necessary when filming movies, television shows, or commercials, when shooting video clips, or when taking still photographs, whether such activities are carried out indoors or outdoors. A desired illumination effect may also be desired for live performances on stage or in any other type of setting.

A primary purpose of a lighting system is to illuminate a subject to allow proper image capture or achieve a desired effect. Often it is desirable to obtain even lighting that minimizes shadows on or across the subject. It may be necessary or desired to obtain lighting that has a certain tone, warmth, or intensity. It may also be necessary or desired to have certain lighting effects, such as colorized lighting, strobed lighting, gradually brightening or dimming illumination, or different intensity illumination in different fields of view.

Various conventional techniques for lighting in the film and television industries, and various illustrations of lighting equipment, are described, for example, in *Lighting for Television and Film* by Gerald Millerson (3rd ed. 1991), hereby incorporated herein by reference in its entirety, including pages 96-131 and 295-349 thereof, and in *Professional Lighting Handbook* by Verne Carlson (2nd ed. 1991), also hereby incorporated herein by reference in its entirety, including pages 15-40 thereof.

As one example illustrating a need for an improved lighting effects system, it can be quite challenging to provide proper illumination for the lighting of faces in television and film, especially for situations where close-ups are required. Often, certain parts of the face must be seen clearly. The eyes, in particular, can provide a challenge for proper lighting. Light reflected in the eyes is known as "eye lights" or "catch lights." Without enough reflected light, the eyes may seem dull. A substantial amount of effort has been expended in constructing lighting systems that have the proper directivity, intensity, tone, and other characteristics to result in aesthetically pleasing "eye lights" while also meeting other lighting requirements, and without adversely impacting lighting of other features.

Because of the varied settings in which lighting systems are used, the conventional practice in the film, commercial, and related industries is for a lighting system, when needed, to be custom designed for each shoot. This practice allows the director or photographer to have available a lighting system that is of the necessary size, and that provides the desired

2

intensity, warmth, tone and effects. Designing and building customized lighting systems, however, is often an expensive and time-consuming process.

The most common lighting systems in film, commercial, and photographic settings use either incandescent or fluorescent light elements. However, conventional lighting systems have drawbacks or limitations which can limit their flexibility or effectiveness. For example, incandescent lights have been employed in lighting systems in which they have been arranged in various configurations, including on ring-shaped mounting frames. However, the mounting frames used in incandescent lighting systems are often large and ponderous, making them difficult to move around and otherwise work with. A major drawback of incandescent lighting systems is the amount of heat generating by the incandescent bulbs. Because of the heat intensity, subjects cannot be approached too closely without causing discomfort to the subject and possibly affecting the subject's make-up or appearance. Also, the heat from the incandescent bulbs can heat the air in the proximity of the camera; cause a "wavering" effect to appear on the film or captured image. Incandescent lighting may cause undesired side effects when filming, particularly where the intensity level is adjusted. As the intensity level of incandescent lights change, their hue changes as well. Film is especially sensitive to these changes in hue, significantly more so than the human eye.

In addition to these problems or drawbacks, incandescent lighting systems typically draw quite a bit of power, especially for larger lighting systems which may be needed to provide significant wide area illumination. Incandescent lighting systems also generally require a wall outlet or similar standard source of alternating current (AC) power.

Fluorescent lighting systems generate much less heat than incandescent lighting systems, but nevertheless have their own drawbacks or limitations. For example, fluorescent lighting systems, like incandescent lighting systems, are often large and cumbersome. Fluorescent bulbs are generally tube-shaped, which can limit the lighting configuration or mounting options. Circular fluorescent bulbs are also commercially available, and have been used in the past for motion picture lighting.

A major drawback with fluorescent lighting systems is that the low lighting levels can be difficult or impossible to achieve due to the nature of fluorescent lights. When fluorescent lights are dimmed, they eventually begin to flicker or go out as the supplied energy reaches the excitation threshold of the gases in the fluorescent tubes. Consequently, fluorescent lights cannot be dimmed beyond a certain level, greatly limiting their flexibility. In addition, fluorescent lights suffer from the same problem as incandescent lights when their intensity level is changed; that is, they tend to change in hue as the intensity changes, and film is very sensitive to alterations in lighting hue.

Typically, incandescent or fluorescent lighting systems are designed to be placed off to the side of the camera, or above or below the camera. Because of such positioning, lighting systems may provide uneven or off-center lighting, which can be undesirable in many circumstances.

Because of their custom nature, both incandescent lighting systems and fluorescent lighting systems can be difficult to adapt to different or changing needs of a particular film project or shoot. For example, if the director or photographer decides that a different lighting configuration should be used, or wants to experiment with different types of lighting, it can be difficult, time-consuming, and inconvenient to re-work or modify the customized lighting setups to provide the desired effects. Furthermore, both incandescent lighting systems and

fluorescent lighting systems are generally designed for placement off to the side of the camera, which can result in shadowing or uneven lighting.

A variety of lighting apparatus have been proposed for the purpose of inspecting objects in connection with various applications, but these lighting apparatus are generally not suitable for the movie, film or photographic industries. For example, U.S. Pat. No. 5,690,417, hereby incorporated herein by reference in its entirety, describes a surface illuminator for directing illumination on an object (i.e., a single focal point). The surface illuminator has a number of light-emitting diodes (LEDs) arranged in concentric circles on a lamp-supporting housing having a circular bore through which a microscope or other similar instrument can be positioned. The light from the LEDs is directed to a single focal point by either of two methods. According to one technique disclosed in the patent, a collimating lens is used to angle the light from each ring of LEDs towards the single focal point. According to another technique disclosed in the patent, each ring of LEDs is angled so as to direct the light from each ring on the single focal point.

Other examples of lighting apparatus used for the purpose of inspecting objects are shown in U.S. Pat. Nos. 4,893,223 and 5,038,258, both of which are hereby incorporated herein by reference in their entirety. In both of these patents, LEDs are placed on the interior of a spherical surface, so that their optical axes intersect at a desired focal point.

Lighting apparatus specially adapted for illumination of objects to be inspected are generally not suitable for the special needs of the film, commercial, or photographic industries, or with live stage performances, because the lighting needs in these fields differs substantially from what is offered by object inspection lighting apparatus. For example, movies and commercials often require illumination of a much larger area that what object inspection lighting systems typically provide, and even still photography often requires that a relatively large subject be illuminated. In contrast, narrow-focus lighting apparatuses are generally designed for an optimum working distance of only a few inches (e.g., 3 to 4 inches) with a relatively small illumination diameter.

Still other LED-based lighting apparatus have been developed for various live entertainment applications, such as theaters and clubs. These lighting apparatus typically include a variety of colored LEDs in hues such as red, green, and blue (i.e., an "RGB" combination), and sometimes include other intermixed bright colors as well. These types of apparatus are not well suited for applications requiring more precision lighting, such as film, television, and so on. Among other things, the combination of red, green, and blue (or other) colors creates an uneven lighting effect that would generally be unsuitable for most film, television, or photographic applications. Moreover, most of these LED-based lighting apparatus suffer from a number of other drawbacks, such as requiring expensive and/or inefficient power supplies, incompatibility with traditional AC dimmers, lack of ripple protection (when connected directly to an AC power supply), and lack of thermal dissipation.

In the context of film and television, various attempts have been made to develop camera-mounted lighting fixtures; however, prior attempts to provide a suitable camera-mounted lighting fixture suffer from a variety of potential drawbacks. For example, conventional camera-mounted lighting fixtures using incandescent or fluorescent lighting elements suffer from the same drawbacks as described above, and can cause undesirable shadowing or other side effects. Also, camera-mounted lighting fixtures which are designed to connect to the camera's battery can cause premature depletion

of the battery. Other lighting fixtures are designed to be powered by a battery pack which is worn, typically on a belt, by the camera operator. Such battery belts are often heavy and cumbersome, and may require lengthy power cords that can interfere with camera maneuverability.

It would therefore be advantageous to provide a lighting apparatus or lighting effects system that is versatile and portable, and may find use in a variety of applications. It would further be advantageous to provide a lighting apparatus or lighting effects system that is well suited for use in the film, commercial, and/or photographic industries, and/or with live stage performances, that overcomes one or more of the foregoing disadvantages, drawbacks, or limitations.

SUMMARY OF THE INVENTION

The invention is generally directed in one aspect to a novel and versatile lighting apparatus. According to one embodiment as disclosed herein, a lighting apparatus comprises a light panel having a panel frame, with a plurality of semiconductor light elements, such as LEDs, secured to the panel frame. A self-contained battery unit securably attaches to the outside of the panel frame. When attached together, the light panel and self-contained battery unit function as an integrated lighting apparatus. Optionally, the light panel may have an integrated dimmer switch, and may also be capable of receiving power from a source other than the self-contained battery unit.

In various forms and embodiments, the lighting apparatus may be adapted for being mounted to a camera or a stand, and may include adapters for such a purpose. The lighting apparatus may also be provided with a diffusion lens or color gels, which may be integrated with or detachable from the light panel. The lighting apparatus may conveniently be provided in the form of a kit, with one or more of a light panel, self-contained battery unit, compact stand, connecting cable(s), adapter(s), lenses or color gels, and so on, being provided in a single package to allow flexibility and versatility to users in the field.

Further embodiments, variations and enhancements are also disclosed herein.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a diagram of an example of a lighting effects system in accordance with one embodiment as disclosed herein, illustrating placement of a camera relative to a lighting frame.

FIG. 2 is a block diagram of a lighting effects system showing various components of a preferred system.

FIG. 3 is an oblique view diagram illustrating an example of attachment of one type of camera mounting assembly to a particular type of lighting assembly frame.

FIG. 4 is a front view diagram of a lighting assembly frame with small, low-power lamps to provide illumination arranged in a preferred pattern.

FIG. 5 is a diagram illustrating aspects of the lighting effect provided by a lighting assembly such as, for example, shown in FIG. 4.

FIG. 6 is a diagram illustrating various human eye features that may be of interest in providing illumination for films, commercials or photography.

FIG. 7 is a diagram of a light segment as may be used, for example, with the lighting assembly of FIG. 4, along with filtering lens(es).

FIG. 8 is a diagram illustrating the effect of a filtering lens on an individual light element.

5

FIG. 9 is a graph illustrating a frequency distribution of light in accordance with one lighting effects system embodiment as disclosed herein.

FIGS. 10A and 10B are a block diagrams of two different types of electronic controllers as may be employed, for example, in the lighting effects system illustrated in FIG. 2.

FIG. 11 is an oblique view diagram of another embodiment of a lighting assembly frame as disclosed herein.

FIG. 12 is a diagram illustrating various options and accessories as may be used in connection with the lighting assembly frame depicted in FIG. 11.

FIG. 13 is a diagram of electronic control circuitry as may be employed, for example, with the lighting effects system illustrated in FIG. 11.

FIG. 14 is a graph illustrating a frequency distribution of light in accordance with another lighting effects system embodiment as disclosed herein.

FIGS. 15A and 15B are diagrams showing an oblique view and a top view, respectively, of a portion of a lighting assembly frame.

FIG. 15C is a diagram illustrating assembly of a lighting assembly frame from two halves thereof.

FIGS. 16A and 16B are diagrams showing an oblique view and a top view, respectively, of the backside of the lighting assembly frame portion illustrated in FIGS. 15A and 15B, while FIGS. 16C, 16D and 16E are diagrams showing details of the lighting assembly frame portion shown in FIGS. 16A and 16B.

FIG. 17 is a diagram of a cover as may be used in connection with the lighting effects system of FIG. 2 or the frame assembly of FIG. 4.

FIG. 18 is a diagram of a portion of a preferred camera mounting assembly.

FIGS. 19A and 19B are diagrams collectively illustrating another portion of a preferred camera mounting assembly.

FIG. 20 is a diagram of a retention clip for a camera mounting assembly.

FIG. 21 is a diagram of a plunger used in connection with attaching a mounting assembly to a lighting frame, in accordance with one technique as disclosed herein.

FIG. 22 is a diagram of a mounting assembly with components from FIGS. 18 and 19 shown assembled.

FIG. 23 is a diagram illustrating one technique for attaching a camera mounting assembly to a lighting frame.

FIGS. 24, 25 and 26 are diagram of components relating to another type of camera mounting assembly.

FIG. 27 is a diagram showing components of FIGS. 24, 25 and 26 assembled together.

FIGS. 28 and 29 are diagrams of alternative embodiments of integral or semi-integral camera mounting assemblies.

FIGS. 30A, 30B and 30C are diagrams illustrating various alternative lamp patterns.

FIG. 31 is a diagrams of an LED suitable for surface mounting.

FIG. 32 is a diagram of a lighting array mounted atop a circuit board.

FIG. 33 is a diagram of one embodiment of a lighting effects system having at least two different lamp colors.

FIG. 34 is a diagram of another embodiment of a lighting effects system having at least two different lamp colors.

FIG. 35 is a diagram of a lighting apparatus embodied as a panel having lighting arrays mounted thereon.

FIGS. 36A and 36B are side-view diagrams of two different types of surface-mount LEDs, and FIG. 36C is an oblique image of the LED shown in FIG. 36A.

6

FIG. 37A is a diagram of one embodiment of a lens cap for an LED, and FIGS. 37B and 37C are diagrams illustrating placement of the lens cap with respect to a particular type of LED.

FIGS. 37D and 37E are diagrams illustrating another embodiment of a lens cap for an LED, and placement thereof with respect to a particular type of LED.

FIG. 38A is a front view diagram of a ring-shaped lighting frame assembly with surface-mount LEDs arranged on the lighting frame.

FIG. 38B is a side view diagram of one embodiment of the lighting frame assembly illustrated in FIG. 36A, showing backside fins for heat dissipation.

FIGS. 39 and 40 are diagrams illustrating examples of a panel light with surface mount LEDs.

FIG. 41A is an oblique view diagram of a panel light illustrating backside fins and a groove for attachment to a multi-panel lighting assembly, and FIG. 41B is a diagram of a multi-panel lighting assembly illustrating attachment of the panel light shown in FIG. 41A.

FIG. 42A is a diagram of a detachable integrated lens sheet for a panel light, and FIGS. 42B-42D are more detailed diagrams of portions of the integrated lens sheet.

FIG. 43 is a diagram of a multi-panel lighting assembly employed on a lighting stand.

FIG. 44 is a cross-sectional diagram illustrating an adjustable lens cover of the type shown in FIG. 12, and an optional mechanism for securing interiorly positioned color gel(s) and/or lens filter(s).

FIG. 45 is a diagram of a flexible LED strip with surface mount LEDs.

FIG. 46 is a diagram of a ring-shaped lighting frame assembly with multiple fluorescent lights.

FIGS. 47A and 47B are diagrams of a lighting apparatus in accordance with one embodiment as disclosed herein.

FIGS. 48A and 48B are diagrams of the lighting apparatus in FIGS. 47A-B together with an attachable battery unit.

FIGS. 49A and 49B are diagrams showing attachment of the lighting apparatus in FIGS. 47A-B and 48A-B to the attachable battery unit of FIGS. 48A-B.

FIG. 50A is a diagram illustrating placement of a lens and optional color gel on the integrated light panel and battery apparatus of FIGS. 48A-B, and FIG. 50B is a side view diagram illustrating the lens in place.

FIG. 51 is a diagram showing one possible means for mounting an LED light panel to a camera.

FIGS. 52A, 52B and 52C are diagrams illustrating attachment of various mounting pins to the lighting apparatus shown in FIGS. 47A-B.

FIGS. 53A through 53D are diagrams showing different views of an integrated LED light panel and battery apparatus mounted on a stand.

FIG. 54 is a diagram showing details of one possible mounting arm configuration for the stand illustrated in FIGS. 53A-D.

FIG. 55 is a diagram of a light panel attached to a stand.

FIG. 56 is a simplified block diagram illustrating components of a battery unit in accordance with one embodiment as disclosed herein.

FIG. 57 is a functional block diagram illustrating circuits or components of an LED light panel in accordance with one embodiment as disclosed herein.

FIG. 58 is a diagram of an alternative embodiment of a battery unit, including an adapter panel and at least one attachable battery.

FIG. 59 is a diagram illustrating a panel light with one or more adapters for mounting or affixing the panel light.

FIGS. 60 and 61 are diagrams of a panel light mounted to different types of tripods.

FIG. 62 is a diagram of a stackable panel light, shown mounted on a stand.

FIGS. 63A and 63B are diagrams of an embodiment of a camera-mountable lighting apparatus.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENT(S)

Before describing preferred embodiment(s) of the present invention, an explanation is provided of several terms used herein.

The term "lamp element" is intended to refer to any controllable luminescent device, whether it be a light-emitting diode ("LED"), light-emitting electrochemical cell ("LEC"), a fluorescent lamp, an incandescent lamp, or any other type of artificial light source. The term "semiconductor light element" or "semiconductor light emitter" refers to any lamp element that is manufactured in whole or part using semiconductor techniques, and is intended to encompass at least light-emitting diodes (LEDs) and light-emitting electrochemical cell (LECs).

The term "light-emitting diode" or "LED" refers to a particular class of semiconductor devices that emit visible light when electric current passes through them, and includes both traditional low power versions (operating in, e.g., the 20 mW range) as well as high output versions such as those operating in the range of 3 to 5 Watts, which is still substantially lower in wattage than a typical incandescent bulb. Many different chemistries and techniques are used in the construction of LEDs. Aluminum indium gallium phosphide and other similar materials have been used, for example, to make warm colors such as red, orange, and amber. A few other examples are: indium gallium nitride (InGaN) for blue, InGaN with a phosphor coating for white, and Indium gallium arsenide with Indium phosphide for certain infrared colors. A relatively recent LED composition uses Indium gallium nitride (InGaN) with a phosphor coating. It should be understood that the foregoing LED material compositions are mentioned not by way of limitation, but merely as examples.

The term "light-emitting electrochemical cell" or LEC" refers to any of a class of light emitting optoelectronic devices comprising a polymer blend embeded between two electrodes, at least one of the two electrodes being transparent in nature. The polymeric blend may be made from a luminescent polymer, a salt, and an ion-conducting polymer, and various different colors are available. Further background regarding LECs may be found, for example, in the technical references D. H. Hwang et al, "New Luminescent Polymers for LEDs and LECs," Macromolecular Symposia 125, 111 (1998), M. Gritsch et al, "Investigation of Local Ions Distributions in Polymer Based Light Emitting Cells," Proc. Current Developments of Microelectronics, Bad Hofgastein (March 1999), and J. C. deMello et al, "The Electric Field Distribution in Polymer LECs," Phys. Rev. Lett. 85(2), 421 (2000), all of which are hereby incorporated by reference as if set forth fully herein.

The term "color temperature" refers to the temperature at which a blackbody would need to emit radiant energy in order to produce a color that is generated by the radiant energy of a given source, such as a lamp or other light source. A few color temperatures are of particular note because they relate to the film and photographic arts. A color temperature in the range of 3200° Kelvin (or 3200° K) is sometimes referred to as "tungsten" or "tungsten balanced." A color temperature of "tungsten" as used herein means a color temperature suitable

for use with tungsten film, and, depending upon the particulars of the light source and the film in question, may generally cover the color temperature range anywhere from about 1000° Kelvin to about 4200° Kelvin. A color temperature in the range of 5500° Kelvin (or 5500° K) is sometimes referred to as "daylight" or "daylight balanced." Because the color of daylight changes with season, as well as changes in altitude and atmosphere, among other things, the color temperature of "daylight" is a relative description and varies depending upon the conditions. A color temperature of "daylight" as used herein means a color temperature suitable for use with daylight film, and, depending upon the particulars of the light source and the film in question, may generally cover the color temperature range anywhere from about 4200° Kelvin to about 9500° Kelvin.

In one embodiment, a lighting effects system comprises an arrangement of lamp elements on a panel or frame. The lamp elements may be embodied as low power lights such as light-emitting diodes (LEDs) or light emitting electrochemical cells (LECs), for example, and may be arranged on the panel or frame in a pattern so as to provide relatively even, dispersive light. The panel or frame may be relatively lightweight, and may include one or more circuit boards for direct mounting of the lamp elements. A power supply and various control circuitry may be provided for controlling the intensities of the various lamp elements, either collectively, individually, or in designated groups, and, in some embodiments, through pre-programmed patterns.

In another embodiment, a lighting effects system comprises an arrangement of low power lights mounted on a frame having an opening through which a camera can view. The low power lights may be embodied as LEDs or LECs, for example, arranged on the frame in a pattern of concentric circles or other uniform or non-uniform pattern. The frame preferably has a circular opening through which a camera can view, and one or more mounting brackets for attaching the frame to a camera. The low power lights may be electronically controllable so as to provide differing intensity levels, either collectively, individually, or in designated groups, and, in some embodiments, may be controlled through pre-programmed patterns.

FIG. 1 is a diagram of an example of a preferred lighting effects system 100 in accordance with one embodiment as disclosed herein, illustrating placement of a camera 140 relative to a lighting frame 102. The lighting frame 102 shown in FIG. 1 may be generally ring-shaped (as shown in, for example, FIGS. 3 and 4, and later described herein), and may define a central hole 103 through which the camera 140 can view. The camera 140 itself, while illustrated in FIG. 1 as a motion picture type camera, may be embodied as any type of image capture or optical viewing device, whether analog or digital in nature. For example, the camera 140 may use film or solid state image capture circuitry (e.g., CCDs), and may be a still photography camera or a motion picture camera. In a preferred embodiment, the lighting frame 102 is physically attached to the camera 140 using a camera mounting, as further described herein.

FIG. 2 is a block diagram of a lighting effects system 200 that may, if desired, be constructed in accordance with various principles illustrated in or described with respect to FIG. 1. As illustrated in FIG. 2, the lighting effects system 200 comprises a lighting frame 202 upon which are mounted or otherwise affixed a plurality of lamps 205. Preferred arrangements of the lamps 205 are described further herein. The lighting frame 202 may include a mounting assembly receptor 220 for receiving a mounting assembly 230 (preferably removable in nature), and an electrical socket 215 for receiv-

ing a cable **213** providing electrical power to the lamps **205** from a power source **210**, although in alternative embodiments battery power may be used. A power controller **212** is preferably interposed between the power source **210** and the electrical socket **215**, for providing various lighting effect functions described in more detail hereinafter, such as, for example, dimming, strobing, selective activation, pulsation, and so on, or combinations thereof.

In a preferred embodiment, the lighting frame **202** is ring-shaped, and the lamps **205** are arranged in a pattern around the center hole of the lighting frame **202** so as to provide the desired lighting condition—typically, the lamps **205** will be arranged in a symmetrical, regular pattern so as to provide relatively even lighting over the area of interest. The lighting frame **202** is preferably comprised of a lightweight, durable material, such as thermoplastic and/or aluminum, with a flat black finish (either paint, coating or material) so as to eliminate any reflections from the front of the lighting frame **202** that might cause ghosts to the final image.

An example of a preferred lighting frame **302** is depicted from various angles in FIGS. **3** and **4**. FIG. **4** shows a front view of a lighting frame **302**, illustrating the preferred ring-shaped nature thereof. In the embodiment shown in FIG. **4**, a number of lamp segments **306** are arranged in a radial or arrayed pattern around the center hole **303** of the lighting frame **302**. The lamp segments **306** are positioned along rays **308** emanating from a center point **307** of the lighting frame **302**, and are preferably equidistant from one another (i.e., the rays **308** are preferably defined such that all of the angles between neighboring rays **308** are equal). The equidistant placement of the lamp segments **306** results in a symmetrical, even pattern that advantageously provides even lighting over an area of interest.

The density of the lamp pattern may vary, and is dictated in part by the particular lighting needs. Examples of alternative lamp arrangement patterns are shown in FIGS. **30A-30C**. FIGS. **30A** and **30B** show the lighting frame **302** with different pattern densities of lamp segments **306**. FIG. **30C** illustrates a lamp pattern in which pairs **309** of lamp segments **306** are arranged near adjacent to one another, while each pair **309** of lamp segments **306** is positioned further away from its neighboring pair **309** than from the other lamp segment **306** that is part of the lamp segment pair **309**. The lamp patterns shown in FIGS. **30A**, **30B** and **30C** are meant to be merely illustrative and not exhaustive. Other lamp patterns might involve, for example, triplets of lamp segments (rather than pairs or singles), or alternating single lamps with pairs and/or triplets, or lamp segments which have gradually increasing or decreasing spacing between them, or lamp segment clusters having the same or different numbers of lamp segments in each cluster, to name a few. The lamp pattern can thus be varied to suit the particular lighting needs, but is preferably symmetric at least in those situations calling for even lighting over the area of interest.

Each of the lamp segments **306** preferably comprises a plurality of low power lamps **305**, such as illustrated, for example, in FIG. **4**. The low power lamps are preferably solid state in nature and may comprise, for example, light-emitting diodes (LEDs), light-emitting crystals (LECs), or other low power, versatile light sources. Alternatively, fluorescent lamps may be used instead of lamp segments, as described later herein, for example, with respect to, e.g., FIG. **13**. Fluorescent lights are power efficient and tend to have high concentrations or spikes of blue, green, and ultraviolet wavelength light. Most white LEDs have color spikes as well. These spikes of color combined with improper proportions of other wavelengths can render the colors of objects seen or

photographed as incorrect or odd in hue. Slight color variations may be added relatively easily to the lenses of LEDs to compensate for these deficiencies without significantly impacting the overall light output. Colored LED lenses may also be used to generate a desired color (such as red, green, etc.), but, since colored lenses are subtractive in nature, the stronger the color, generally the more the output of the LED will be dimmed. White LEDs typically utilize clear or nearly clear lenses; however, in any of the embodiments described herein, a clear LED lens may be manufactured with slight subtractive characteristics in order to minimize any color spikes and/or non-linearities in the output of an LED.

The number of low power lamps **305** in each lamp segment **306** may be the same or may vary among lamp segments **306**. If the number of low power lamps **305** is the same in each lamp segment **306** and are spaced the same (for example, equidistant from one another) within each lamp segment **306**, then the resulting pattern will be a plurality of concentric circles of low power lamps **305** radiating outward from the inner circular portion to the outer circular portion of the lighting frame **302**. It will be appreciated, however, that the low power lamps **305** need not be arranged in segments **306** as illustrated in FIG. **4**, but may be arranged in clusters or other patterns, whether uniform or non-uniform, over the lighting frame **302**. However, a symmetrical, regular pattern of low power lamps **305** is preferred, at least where uniform lighting is desired over an area of interest.

FIG. **5** illustrates the effect of a lighting frame assembly such as light frame **302** with low power lamps **305** arranged as shown in FIG. **4**, in illuminating a subject **646**. As shown in FIG. **5**, radiating light regions **620**, **621** from lamps arranged on the front surface of the lighting frame **302** (as illustrated in FIG. **4**, for example) overlap one another in a manner so as to provide lighting from multiple angles. With a radial or arrayed pattern of lamp segments **306** as shown in FIG. **4**, a subject **646** may be relatively evenly illuminated from every angle. FIG. **1** illustrates a preferred placement of a camera **140** (including any type of image capture device, whether film based, solid state/CCD, or otherwise) with respect to a lighting frame **102** (which may be embodied, for example, as lighting frame **302**). As illustrated in FIG. **1**, the camera **140** may be positioned so that its lens or optical front-end peers through the central hole **103** of the lighting frame **102**, thus allowing the lighting to be presented from the same angle and direction as the camera viewpoint.

FIG. **6** illustrates how the lighting frame assembly with the pattern of lamp segments **306** as shown in FIG. **4** may advantageously illuminate a human subject's eyes. In FIG. **6**, the iris **650** of the subject's eye **654** is illustrated showing a circular pattern of reflected light segments **652** around the iris **650**. A lighting pattern of a lighting system such as illustrated in FIG. **4** can illuminate the iris **650** of the subject's eye **654** from multiple angles, thus helping provide desirable "eye lights" or "catch lights" with respect to a human subject **546**, as well as providing uniform, even lighting over the area of interest.

Turning once again to FIG. **3**, an oblique view of the lighting frame **302** is shown illustrating an example of attachment of one type of camera mounting assembly **330** to the lighting frame **302**. In the particular embodiment illustrated in FIG. **3**, a mounting assembly receptor **320** is affixed to, molded as part of, or otherwise attached to the lighting frame **302**. The camera mounting assembly **330** is preferably configured so as to attach securely to the mounting assembly receptor **320**. The mounting assembly receptor **320** may, for example, include a socket **323** or similar indentation adapted to receive a corresponding member **335** on the camera mount-

11

ing assembly **330**. The member **335** may be attached to an elongated rod or arm **332**, along which a camera clamp **334** may be slidably engaged. The camera clamp **334** preferably includes a generally U-shaped clamping portion **336** which may be securely attached along the housing of a camera, and may advantageously be moved along the elongated rod or arm **332** and clamped into a suitable position using a clamping screw or other fastening mechanism.

FIGS. **15A** and **15B** are diagrams showing an oblique view and a frontal view, respectively, of one portion of a lighting assembly frame **1502** in accordance with one or more of the concepts or principles explained with respect to the embodiment shown in FIG. **3**. As illustrated in FIGS. **15A** and **15B**, the lighting assembly frame portion **1502** is generally ring-shaped in nature, having a central hole **1503** for allowing a camera or other image capture device to view through the lighting assembly frame. The lighting assembly frame portion **1502** may be reinforced, if desired, with ribs **1560**, and may include, as noted with respect to FIG. **3**, a mounting assembly receptor **1520** for receiving a camera mounting assembly (not shown in FIG. **15A**), and an electrical socket **1515** for receiving a cable or wires for providing power to the lamps of the lighting assembly.

The lighting frame portion **1502** illustrated in FIG. **15A** comprises one half (specifically, the backside half) of a complete lighting frame assembly. A corresponding lighting frame portion **1592** (e.g., printed circuit board), as shown in FIG. **15C**, may be adapted to fit securely to the lighting frame portion **1502** (e.g., injected molded poly-carbonate), and may attach thereto by, for example, exterior locking tabs **1564** and/or interior locking tabs **1567**, which are shown in FIGS. **15A** and **15B**. Alternatively, other means for fastening together the lighting frame assembly **1501** may be used, such as screws, glue, etc.

Likewise, the mounting assembly receptor **1520** may comprise any suitable mechanism for securing a camera mounting assembly to the lighting frame portion **1502** of the lighting frame assembly **1501**. In the example illustrated in FIGS. **15A** and **15B**, the mounting assembly receptor **1520** may comprise a raised, slightly tapered cylindrical housing, defining a hollow cylindrical chamber in which the camera mounting assembly may be fitted. If the lighting frame portion **1502** is formed of plastic, for example, then the mounting assembly receptor **1520** may be formed through an injection molding process. FIG. **18** depicts an example of a portion of a camera mounting assembly **1801** as may be affixed to the lighting frame portion **1502** using the mounting assembly receptor **1520**. The camera mounting assembly **1801** in FIG. **18** comprises an elongated rod or arm **1832**, at the end of which is affixed an attachment member **1835** having a generally circular body portion with two wing-like protruding tabs **1838**. The tabs **1838** may be fitted into two corresponding indentations **1524** in the ring-shaped top surface of the cylindrical housing of the mounting assembly receptor **1520**. The camera mounting assembly **1801** may then be twisted in a clockwise direction to cause the tabs **1838** to slide through the slits adjacent to the indentations **1524** in the mounting assembly receptor **1520**, allowing the camera mounting assembly **1801** to be slid downward, then twisted in a counter-clockwise direction and locked into place in the mounting assembly receptor **1520**. The camera mounting assembly **1801** may be disengaged from the lighting frame portion **1501** by manually applying pressure to release the locking tabs and twisting the camera mounting assembly **1801** in the opposite (i.e., clockwise in this example) direction from that originally used to bring it into a locking position. The camera mounting assembly **1801** may then be raised upwards and twisted in a counter-

12

clockwise direction to cause the tabs **1838** to slide back through the slits adjacent to the indentations **1524** in the mounting assembly receptor **1520**, thereby completely releasing the camera mounting assembly **1801**.

A variety of other means may alternatively be used to affix a camera mounting assembly to the lighting frame portion **1502**, but the mechanism used in the embodiment depicted in FIGS. **15A** and **15B** has the advantage of not requiring additional pieces (such as screws), and being relatively simple and quick to use.

A main purpose of the camera mounting assembly **1801** is to allow the lighting frame assembly to be secured to a camera or other image capture device, thus providing even lighting from all directions surrounding the camera or other image capture device, and allowing, for example, the lighting frame assembly to follow the motion of the camera or other image capture device as it is moved. An example of additional components allowing the camera mounting assembly **1801** to be secured to a camera are shown in FIGS. **19A** and **19B**. In particular, FIGS. **19A** and **19B** depict two halves **1902**, **1912** of a camera clamp which may be joined together and attached to the elongated rod or arm **1832** of the camera mounting assembly **1801**, arriving at a complete camera mounting assembly such as illustrated in FIG. **3** (i.e., camera mounting assembly **330**) or, in more detail, in FIG. **22**. The rectangular openings **1903**, **1913** in the two halves **1902** and **1912**, respectively, of the camera clamp allow it to be slid onto the elongated rod or arm **1832**. A spring-loaded retention clip, as shown in FIG. **20**, may be used to help secure the camera clamp to the elongated rod or arm **1832**. In alternative embodiments, the camera clamp (comprising the combination of two halves **1902**, **1912**) may be permanently affixed and/or integrally formed with the elongated rod or arm **1832**.

An attachment member, such as pre-molded clamping member **1916** shown in FIG. **19B**, may be used to slide onto an appropriate feature of the camera (such as a Panavision® type motion picture camera), e.g., a rod or other feature of the camera. Other types of attachment members may be used, depending upon the particular nature of the camera or other image capture device. The camera mounting assembly **1801**, in conjunction with the preferred camera clamp illustrated in FIGS. **19A** and **19B**, thereby allow a lighting frame assembly to be secured to a camera or other image capture device.

FIG. **23** is a diagram illustrating one technique for attaching a camera mounting assembly to a lighting frame. As shown in FIG. **23**, a lighting frame **1302** may comprise a mounting assembly receptor **1320**, similar to as described with respect to FIG. **3** and FIGS. **15A-15B**, for example. In connection with attaching a camera mounting assembly **2328**, a spring **2305** is first positioned in the mounting assembly receptor **2320**, atop of which is then placed a plunger **2308** (such as illustrated in FIG. **21**). Then, the camera mounting assembly **2328** is attached, by, e.g., inserting the attachment member into the mounting assembly receptor **2320**. In essence, the application of the attachment member to the mounting assembly receptor **2320** may be viewed analogously to inserting and twisting a "key" in a keyhole. The spring **2305** effectively locks the camera mounting assembly **2328** in place against the back "keyplate" surrounding the keyhole, thus allowing the camera mounting assembly **2328** to be "twist-locked" into place. The assembly structure shown in FIG. **23** allows relatively easy attachment and detachment of the camera mounting assembly **2328**. Other attachment techniques may also be used.

Another embodiment of a camera mounting assembly, as may be used to attach a lighting frame to a camera or other image capture device, is illustrated in FIG. **27**, and various

13

components thereof are illustrated individually in FIGS. 24, 25 and 26. With reference first to FIG. 24, two halves 2415, 2418 of a camera clamp may be joined together to form a main camera clamp body. the two halves 2415, 2418 may be secured together by screws or any other suitable fastening means. A slot in the camera clamp body may be provided to allow placement of a thumbwheel 2604 (illustrated in FIG. 26) which allows tightening of a clamping member 2437. Several holes 2430 are provided in camera clamp portion 2415, which receive corresponding protrusions 2511 from an attachment member 2501, illustrated in FIG. 25, which has a generally circular body portion 2519 with two wing-like protruding tabs 2586. The completed camera mounting assembly 2701 appears as in FIG. 27.

The tabs 2586 of the camera mounting assembly 2701 shown in FIG. 27 may be fitted into the two corresponding indentations 1524 in the ring-shaped top surface of the cylindrical housing of the mounting assembly receptor 1520 shown in FIG. 15, as described previously with respect to the FIG. 22 camera mounting assembly. As before, the camera mounting assembly may be twisted in a clockwise direction to cause the tabs 2586 to slide through the slits adjacent to the indentations 1524 in the mounting assembly receptor 1520, allowing the camera mounting assembly 2701 to be slid downward, then twisted in a counter-clockwise direction and locked into place in the mounting assembly receptor 1520. The camera mounting assembly 2701 may be disengaged from the lighting frame portion 1501 by manually applying pressure to release the locking tabs and twisting the camera mounting assembly 2701 in the opposite (i.e., clockwise in this example) direction from that originally used to bring it into a locking position. The camera mounting assembly 2701 may then be raised upwards and twisted in a counter-clockwise direction to cause the tabs 2586 to slide back through the slits adjacent to the indentations 1524 in the mounting assembly receptor 1520, thereby completely releasing the camera mounting assembly 2701.

As noted previously, a variety of other means may alternatively be used to affix a camera mounting assembly 2701 of FIG. 27 to the lighting frame portion 1502.

As with the camera mounting assembly 1801 shown in FIG. 18, the camera mounting assembly of FIG. 27 functions to allow a lighting frame assembly to be secured to a camera or other image capture device, thus allowing, for example, the lighting frame assembly to follow the motion of the camera or other image capture device as it is moved. An attachment member, such as pre-molded clamping member 2437 shown in FIG. 24, may be used to slide onto an appropriate feature, such as a rod or other feature, of the camera (for example, an Arri® type motion picture camera).

FIGS. 28 and 29 are diagrams of alternative embodiments of camera mounting assemblies having certain integral components. FIG. 28 illustrates a camera mounting assembly 2801 as may be used, for example, to secure a lighting frame to a Panavision® type camera. As shown in FIG. 28, an attachment member 2838 (or “key”) connects with, and integrally attaches to, a camera clamp plate 2802, in a manner similar to that shown in FIG. 18, but eliminating the elongated rod or arm shown therein. A pair of cylindrically-shaped lock lever “screws” 2851, 2852 enable the camera mounting assembly 2801 to attach to an appropriate feature of the camera. Lock levers 2855, 2856 connected to each of the lock lever screws 2851, 2852 can be flipped (e.g., a quarter turn) in order to lock the screws 2851, 2852 into place, thus securing the camera mounting assembly 2801 to the camera. The lock lever screws 2851, 2852 can be flipped the opposite direction

14

to unlock the screws 2851, 2852 and thereby release the camera mounting assembly 2801 from the camera.

FIG. 29 illustrates a camera mounting assembly 2901 as may be used, for example, to secure a lighting frame to an Arri® type camera. As shown in FIG. 29, an attachment member 2938 (or “key”) connects with, and attaches to, a camera clamp plate 2902, by way of, e.g., screws 2940. A cylindrically-shaped lock lever screw 2951 enables the camera mounting assembly 2901 to attach to an appropriate feature of the camera. A lock lever 2855 connected to the lock lever screw 2851 can be flipped (e.g., a quarter turn) in order to lock the screw 2851 into place, thus securing the camera mounting assembly 2901 to the camera. The lock lever screw 2851 can be flipped the opposite direction to unlock the screw 2851 and thereby release the camera mounting assembly 2901 from the camera.

Additional details of the particular lighting frame portion 1501 of FIGS. 15A and 15B are illustrated in FIGS. 16A through 16E. FIGS. 16A and 16B, for example, are diagrams showing an oblique view and a top view, respectively, of the backside of the lighting frame portion 1501 illustrated in FIGS. 15A and 15B. In FIGS. 16A and 16B can more clearly be seen, for example, the interior locking tabs 1567 and exterior locking tabs 1564 that can be used to secure the lighting frame portion 1501 to its corresponding half, as previously described with respect to FIG. 15C. In FIG. 16C is depicted a close-up illustration of the backside of the mounting assembly receptor 1520 and electrical socket 1515 illustrated from the opposite side in FIGS. 15A and 15B. In FIGS. 16D and 16E can be seen additional details of both the mounting assembly receptor 1520 (FIG. 16D) and the interior locking tabs 1567 and exterior locking tabs 1564. As shown in FIGS. 16D and 16E, the interior locking tabs 1567 may include a protruding locking member 1570 for securing the lighting frame portion 1501 to its counterpart by, e.g., snapping it into place, and the exterior locking tabs 1564 may likewise include protruding locking members 1568 having a similar function. The frame wall 1562 between the two nearby exterior locking tabs 1564 may be reinforced with a supporting rib 1569, to provide added counter-force when the lighting frame assembly is put together.

The camera mounting assemblies shown in FIGS. 18, 23, 27, 28 and 29 are merely examples of camera mounting assemblies that may be utilized in various embodiments described herein. Other camera mounting assemblies may be specifically adapted to the particular camera of interest. The mounting assembly receptor 320 (or 1520) may in one aspect be viewed as a universal receptor, allowing different camera mounting assemblies to be connected to the lighting frame, provided that they are compatible with the mounting assembly receptor (such as the example shown in FIGS. 15A-15BB and elsewhere). A single lighting frame may thus be used with any of a variety of different cameras or other image capture devices. Although examples have been explained with respect to certain camera types (that is, a Panavision® camera or an Arri® camera), the camera may be of any type, whether for film or still photograph, and may be based upon either analog or digital imaging techniques. Moreover, while preferred dimensions are illustrated in some of the figures, the mounting assemblies and components thereof may be of any appropriate size and shape.

Further description will now be provided concerning various preferred light elements as may be used in connection with one or more embodiments as disclosed herein. While generally discussed with reference to FIG. 3, the various light elements described below may be used in other embodiments as well. When embodied as LEDs, the low power lamps 305

typically will emit light at approximately 7400-7500K degrees when at full intensity, which is white light approximating daylight conditions. However, LEDs of a different color, or one or more different colors in combination, may also be used. FIG. 9 is an energy spectrum graph showing a typical frequency distribution (in terms of light wavelength) of light output from white-light, low voltage LEDs, and illustrating a main peak at about 600 nanometers. A color correction mechanism, such as a color correction gel or lens filter, may be used to alter the color of the LED light. For example, the LED light could be converted to "tungsten daylight" (similar in hue to an incandescent bulb) by use of a color gel or colored lens. A diffusion lens or filter may also be used, by itself or in conjunction with a color gel or colored lens, to diffuse or soften the outgoing light. A diffusion lens or filter may be formed of, e.g., clear or white opaque plastic, and may be configured in a ring-shaped pattern of similar dimension to the light frame 302 to facilitate mounting thereon. FIG. 17, for example, shows a diagram of an opaque, ring-shaped cover 1701 as may be used in connection with the lighting frame assembly depicted in FIG. 3 or FIG. 4.

FIG. 7 is a more detailed diagram of a light segment 792 (e.g., an array) as may be used, for example, in connection with the lighting frame 302 shown in FIG. 4. The light segment 792 may correspond to each of the individual light segments 306 shown in FIG. 4, and the various light elements (i.e., LEDs) 790 in FIG. 7 may correspond to the individual low power lamps 305 shown in FIG. 3. FIG. 7 illustrates a straight row of LEDs 790 as may comprise the lighting segment 790. Although fifteen LEDs 790 are illustrated in the example shown in FIG. 7, any number of LEDs 790 may be used, subject to physical space limitations and lighting intensity requirements. In addition, a set of filtering lenses 794 (which are preferably formed as a single, collective lens comprised of individual lens elements 795 connected together) may be placed over the light segment 792 as shown, such that each lens element 795 is positioned in the light path of one of the LEDs 790. The overall effect can be, for example, to focus or spread the light according to a specifically desired pattern, such as the exemplary light pattern 796 shown in FIG. 7. A variety of other light filtering techniques may also be used.

FIG. 8 is a diagram illustrating the effect of a filtering lens element (e.g., wave guide) 876 on an individual light element (e.g., LED) 872. As shown in FIG. 8, light 874 emanates from the LED 872 in a generally even pattern, but can be focused or otherwise filtered by the filtering lens element 876. FIG. 7 illustrates an example of collectively filtering all of the LEDs 790 of the light segment 792.

Various embodiments of lighting apparatus as described herein utilize different color lamp elements in order to achieve, for example, increased versatility or other benefits in a single lighting mechanism. Among the various embodiments described herein are lamp apparatuses utilizing both daylight and tungsten lamp elements for providing illumination in a controllable ratio. Such apparatuses may find particular advantage in film-related applications where it can be important to match the color of lighting with a selected film type, such as daylight or tungsten.

Alternatively, or in addition, lamp elements of other colorations may be utilized. It is known, for example, to use colored lamp elements such as red, green, and blue LEDs on a single lighting fixture. Selective combinations of red, green, and blue ("RGB") lamp elements can generally be used to generate virtually any desired color, at least in theory. Lighting systems that rely upon RGB lamp elements can potentially be used as primary illumination devices for an image capture system, but suffer from drawbacks. One such problem is

that the red, green, and blue colors generated by the light elements do not necessarily mix completely. The discrete RGB lamp elements (e.g., LEDs) each project a localized "pool" of its individual primary color. This manifests as spots of color, or bands of individual or partially mixed colors. One of the only presently available solutions to correct for this problem is mixing the colors using a diffusion technique. Diffusion mixing can be accomplished by adding detractors, gratings, or white opal-appearing filters, for example. Unfortunately, these techniques end up reducing the overall output of the lighting apparatus and, more importantly, severely reduce the ability of the LEDs to "project" light in a direct fashion. Another problem for illumination systems which rely upon RGB color mixing is that not all of the LEDs are generally used at full power for most lighting situations. One or two of the LED color groups typically have to be dimmed in order for the desired color to be generated, which can further reduce the overall light output. When these factors are considered in combination, RGB based lighting apparatus may not be well suited for providing primary illumination for image capture applications (such as film).

While the foregoing discussion has principally focused on RGB based lighting apparatus, similar problems and drawbacks may be experienced when employing lamp elements in other color combinations as well.

In various embodiments as disclosed herein, a lighting apparatus is provided which utilizes two or more complementary colored lamp elements in order to achieve a variety of lighting combinations which, for example, may be particularly useful for providing illumination for film or other image capture applications. A particular example will be described with respect to a lighting apparatus using lamp elements of two different colors, herein referred to as a "bi-color" lighting apparatus. In a preferred embodiment, the bi-color lighting apparatus utilizes light elements of two different colors which (unlike red, green, and blue) are separated by a relatively small difference in their shift or color balance. When reference is made herein to light elements of two different colors, the light elements may, for example, include a first group which provide light output at a first color and a second group which provide light output at a second color, or else the light elements may all output light of a single color but selected ones of the light elements may be provided with colored LED lenses or filtering to generate the second color. In a preferred embodiment, as will be described, the bi-color lighting apparatus uses lamp elements having daylight and tungsten hues (for example, 5200° K and 3200° K color temperatures, respectively). Other bi-color combinations may also be used and, preferably, other combinations of colors which are closely in hue or otherwise complementary in nature.

One possible advantage of a bi-color lighting system as will be described in certain embodiments below is the ability to more easily blend two similar colors (e.g., 5500 K and 3200 K color temperature hues), particularly when compared to a tri-color (e.g., RGB) lighting system that relies upon opposing or widely disparate colors. The blending process of two similar colors is not nearly as apparent to the eye, and more importantly in certain applications, is a more suitable lighting process for film or video image capture devices. In contrast, attempting to blend 3 primary or highly saturated (and nearly opposite colors) is much more apparent to the eye. In nature one may visually perceive the blending of bi-colors, for example, from an open sky blue in the shade, to the warmth of the direct light at sunset. Such colors are generally similar, yet not the same. Their proportion in relation to each other is a naturally occurring gradient in most every naturally lit situation. This difference is the basis of most photographic and

motion picture lighting hues. These hues give viewers clues as to time of day, location and season. Allowing separate control of the two different color lamp elements (such as LEDs), through two separate circuit/dimmer controls or otherwise, provides the ability to easily adjust (e.g., cross-fade, cross-dim, etc.) between the two colors because they do not have significant color shifts when dimmed and blend in a visually pleasing manner, allowing the type of color gradients that occur in nature. In addition, virtually all still and motion picture film presently used in the industry is either tungsten or daylight balanced, such that various combinations of daylight and tungsten (including all one color) are well matched directly to the most commonly used film stocks. These features make various of the lighting apparatus described herein particularly well suited for wide area still, video, and motion picture usage, especially as compared to RGB-based or other similar lighting apparatus. The above principles may also be extended to lighting systems using three or more lamp element colors.

FIG. 33 is a diagram of one embodiment of a lighting effects system 3300 having at least two different lamp element colors. As illustrated in FIG. 33, the lighting effects system 3300 comprises a lighting frame mounting surface 3302 having a plurality of lamp elements 3305 which, in this example, include daylight LEDs 3304 and tungsten LEDs 3303, although different lamp elements and/or different colors could be chosen. The lighting effects system 3300 further comprises various control electronics for controlling the illumination provided by the lamp elements 3305. In particular, the lighting effects system 3300 comprises an intensity control adjustment 3342, an intensity control circuit 3345, a ratio control adjustment 3341, and a ratio control circuit 3346. The intensity control adjustment 3342 and ratio control adjustment 3341 may each be embodied as, e.g., manual control knobs, dials, switches, or other such means, or alternatively may be embodied as a digital keypad, a set of digital buttons, or the like. A visual display (not shown) such as an LCD display may be provided to allow the operator to view the settings of the intensity control adjustment 3342 and ratio control adjustment 3341. Alternatively, the ratio control adjustment 3341 and/or intensity control adjustment 3342 may comprise digital commands or values received from a computer or similar device.

In operation, setting the intensity control adjustment 3342 selects the illumination level for the lamp elements 3305, while setting the ratio control adjustment 3341 selects the relative intensities between, in this example, the daylight LEDs 3304 and the tungsten LEDs 3303. The intensity control circuit 3352 and ratio control circuit 3346 may comprise analog and/or digital circuitry, and the output of the ratio control circuit 3346 modifies the incoming power supply separately for the daylight LEDs 3304 and the tungsten LEDs 3303 in a manner dictated by the setting of the ratio control adjustment 3341. Accordingly, by use of the ratio control adjustment 3341, the operator may select more daylight illumination by increasing the relative intensity of the daylight LEDs 3304 or may select more tungsten illumination by increasing the relative intensity of the tungsten LEDs 3303. To increase or decrease the overall light output intensity, the operator may adjust the intensity control adjustment 3342. The lighting effects system 3300 thereby may provide different combinations of daylight/tungsten coloration to match a wide variety of settings and circumstances, with the two colors being generally complementary in nature and thus providing a balanced, well blended illumination effect.

FIG. 34 is a diagram of another embodiment of a lighting effects system having at least two different lamp colors. As

illustrated in FIG. 34, and similar to FIG. 33, the lighting effects system 3400 comprises a lighting frame mounting surface 3402 having a plurality of lamp elements 3405 which, in this example, include daylight LEDs 3404 and tungsten LEDs 3403, although different lamp elements and/or different colors could be chosen. The lighting effects system 3400, as with that of FIG. 33, further comprises various control electronics for controlling the illumination provided by the lamp elements 3405. In particular, the lighting effects system 3400 comprises individual intensity control adjustments 3451, 3452 for daylight and tungsten lamp elements (e.g., LEDs) 3403, 3404, and individual intensity control circuits 3456, 3457 also for the daylight and tungsten LEDs 3403, 3404. The tungsten intensity control adjustment 3451 and daylight intensity control adjustment 3452 may, similar to FIG. 33, each be embodied as, e.g., manual control knobs, dials, switches, or other such means, or alternatively may be embodied as a digital keypad, a set of digital buttons, or the like. A visual display (not shown) such as an LCD display may be provided to allow the operator to view the settings of the two intensity control adjustments 3451, 3452. Alternatively, the intensity control adjustments 3451, 3452 may comprise digital commands or values received from a computer or similar device.

In operation, setting the tungsten intensity control adjustment 3451 selects the illumination level for the tungsten LEDs 3403 via the tungsten intensity control circuit 3456, and setting the daylight intensity control adjustment 3452 selects the illumination level for the daylight LEDs 3404 via the daylight intensity control circuit 3457. The relative settings of the tungsten intensity control adjustment 3451 and the daylight intensity control adjustment 3452 generally determine the relative intensities between, in this example, the daylight LEDs 3404 and the tungsten LEDs 3403. The intensity control circuits 3456, 3457 may comprise analog and/or digital circuitry, and the relative outputs of the tungsten intensity control circuit 3456 and the daylight intensity control circuit 3456 generally determine the illumination level and composition. The operator may select more daylight illumination by increasing the relative intensity of the daylight LEDs 3404 or may select more tungsten illumination by increasing the relative intensity of the tungsten LEDs 3403. The lighting effects system 3400 thereby may provide different combinations of daylight/tungsten coloration to match a wide variety of settings and circumstances, as with the FIG. 33 embodiment.

Because the two different colors of LEDs (e.g., daylight and tungsten) can be controlled separately (through common or separate circuitry), and because these particular LEDs, or other similar complementary colors, do not have significant color shifts when dimmed, it would be relatively straightforward to adjust (e.g., cross-fade, cross-dim) between the two colors and, for example, provide a variety of natural light illumination effects for various types of common film stock.

The lighting apparatuses of FIGS. 33 and 34 may, if desired, be physically embodied in a manner as described elsewhere herein; for example, the lighting apparatus may be embodied with a generally ring-shaped lighting frame as illustrated in and/or described with respect to FIG. 4, or with a portable frame such as generally illustrated in and/or described with respect to FIG. 35. The principles and underlying concepts associated with the embodiments of FIGS. 33 and 34 may be extended to support more than two colors of lamp elements 3305 or 3405. Moreover, the lighting apparatuses of FIGS. 33 and 34 may utilize any number of lamp elements in a bi-color or other multi-color arrangement, in any desired pattern.

Returning now to the general diagram of a lighting effects system **201** illustrated in FIG. 2 (although the following comments will apply to various other embodiments such as the lighting frame assembly shown in FIGS. 3 and 4), the LEDs or other low power lamps **205** may be operated at a standard direct current (DC) voltage level, such as, e.g., 12 volts or 24 volts, and may be powered by a power source **210** controlled by a power controller **212** such as generally shown in FIG. 2. The power source **210** can generally comprise a standard electrical outlet (i.e., nominal 110 volt AC power line), although in various embodiments the power source **210** could also be a battery having sufficient current to drive the LEDs or other low power lamps **205**. In some embodiments, the power controller **212** may be omitted, and the lighting frame **202** may be connected directly to the power source **210**.

Block diagrams of two different types of power controllers **212** as may be used in various embodiments as described herein are illustrated in FIGS. 10A and 10B, respectively. With reference to FIG. 10A, a first type of power controller **1012** has an input for receiving an AC power source **1003**, and outputs a plurality of power wires **1047** preferably through a cable (e.g., cable **213** shown in FIG. 2) for connection to the lighting frame **202**. The power controller **1012** may further comprise a power converter **1020**, the nature of which depends upon the type of power source **210**. If the power source is an AC source, the power converter **1020** may comprise an AC-to-DC converter and appropriate step-down power conversion circuitry (e.g., a step-down transformer). On the other hand, if the power source is a DC source (e.g., a battery), the power converter **1020** may comprise a DC-to-DC converter, if necessary. The design and construction of power converters is well known in the field of electrical engineering, and therefore is not described herein in detail.

The power converter **1020** is preferably connected to a plurality of switches **1022**, which may be solid state devices (e.g., transistors) or analog devices (e.g., relays), each switch controlling power delivered by the power converter **1020** to one of the wires **1047** output by the power controller **1012**. A switch selector **1042** controls the on/off state each switch (or group) in the set of switches **1022**. A manual interface **1030** is provided to allow operation of the switches **1022** according to manual selection. The manual interface **1030** may include a master power switch **1031**, switch controls **1032**, and, optionally, an effects selector **1033**. The switch controls **1032** may include an individual manual switch, button or other selection means for each individual switch provided in the set of switches **1022**, or else may comprise a control mechanism (such as knob or reduced number of manual switches, buttons or other selection means) for selecting groups of switches **1022** according to predesignated arrangements. As but one example, assuming a light arrangement such as shown in FIG. 4, a knob provided as part of the switch controls **1032** could have a first setting to select all of the light segments **306**, a second setting to select every other light segment **306**, and a third setting to select every fourth light segment **306**, thus providing options of 100%, 50% and 25% total light output. The switch selector **1042** would then convert each knob setting to a set of control signals to the appropriate switches **1022**, which in turn would control power to the wires **1047** supplying power to the light segments **306**.

As another example, the switch controls **1032** could include an individual manual switch, button or other selection means for each light segment **306** or group of light segments **306** in the lighting arrangement.

An effects generator **1043** may optionally be included in the power controller **1012**, along with an effects selector **1033** which forms part of the manual interface **1030**. The effects

generator **1043** may provide the ability to create various lighting effects, such as, e.g., dimming, strobing, pulsation, or pattern generation. The effects selector **1043** may affect all of the switches **1022** simultaneously, or else may affect individual switches or groups of switches **1022**, depending upon the desired complexity of the lighting effects. Dimming may be accomplished, for example, through a manual control knob or multi-position switch on the effects selector **1033**. The dimming control may be electronically implemented, for example, in an analog fashion through a variable resistive element, or in a digital fashion by detecting the selected manual setting and converting it to selecting power setting through, e.g., selected resistive elements in a resistive ladder circuit. Where the switches **1022** are implemented, for example, as controllable variable amplifiers, the selectable resistance may be used to control the output of each amplifier and thereby the light output by the amplifier's respective light segment **306** (or group of light segments **306**). In other embodiments, the dimming control may optionally be applied to the output of switches **1022**. Where dimming control is applied collectively, it may be implemented by applying the selected dimming control level to the incoming signal from the power converter **1020**, which is supplied to all of the switches **1022** collectively. Other variations for implementing dimming control are also possible and will be apparent to those skilled in the art of electrical engineering.

Strobing may be accomplished by generating an oscillating signal and applying it as a control signal either upstream or downstream from the switch selector **1042**. The frequency of oscillation may be selectable via a manual knob, switch or other selection means as part of the effects selector **1033**.

Pattern generation may be accomplished by, e.g., manual selection from a number of predefined patterns, or else through an interface allowing different pattern sequencing. Patterns may include, for example, strobing or flashing different groups of light segments **306** (given the example of FIG. 3) in a predefined sequence (which may be a pseudo-random sequence, if desired), strobing or flashing different low power lamps **305** of the light segments **306** in a predefined (or pseudo-random) sequence, gradually dimming or brightening the light segments **306** (individually, in groups, or collectively), or various combinations of these effects.

Alternatively, rather than providing a separate effects selector **1033**, certain effects may be combined with the switch controls **1032**. For example, a dimmer switch (knob) could be used to both activate a light segment **306**, or group of light segments **306**, and also control light output via rotation of the dimmer switch (knob).

FIG. 10B is a block diagram showing another example of a power controller **1052** as may be used, for example, in the lighting effects system **200** of FIG. 2 or other embodiments described herein. Like the power controller **1012** shown in FIG. 10A, the power controller **1052** shown in FIG. 10B includes a power source input **1053** connected to a power converter **1060**. It further includes a set of switches **1062** receiving power from the power converter **1060**, and providing power to individual wires **1097** which are conveyed, preferably by cable, to the lighting frame assembly **201** of the lighting effects system **200**. The power controller **1052** also includes a switch selector **1072**, which may comprise, for example, a set of registers which provide digital signals to the switches **1062** to control their on/off state.

The power controller **1052** includes a processor **1074** which may be programmed to provide various lighting effects by manipulating the switch selector **1072** (for example, by changing values in registers which control the on/off states of the switches **1062**). The processor **1074** may interface with a

memory **1075**, which may comprise a volatile or random-access memory (RAM) portion and a non-volatile portion (which may comprise, e.g., ROM, PROM, EPROM, EEPROM, and/or flash-programmable ROM), the latter of which may contain programming instructions for causing the processor **1074** to execute various functions. The memory **1075** may be loaded through an I/O port **1076**, which may include an electrical serial or parallel interface, and/or an infrared (IR) reader and/or bar code scanner for obtaining digital information according to techniques well known in the field of electrical engineering and/or electro-optics. An interface **1080** may also be provided for programming or otherwise interfacing with the processor **1074**, or manually selecting various lighting effects options through selectable knobs, switches or other selection means, as generally explained previously with respect to FIG. **10A**. The processor-based control system illustrated in FIG. **10B** may also include other features and components which are generally present in a computer system.

In operation, the processor **1074** reads instructions from the memory **1075** and executes them in a conventional manner. The instructions will generally cause the processor **1074** to control the switch selector by, e.g., setting various digital values in registers whose outputs control the switches **1062**. The programming instructions may also provide for various lighting effects, such as dimming, strobing, pulsation, or pattern generation, for example. To accomplish dimming, the processor **1074** may be programmed select binary-encoded values to load into registers of the switch selector **1072**, which in turn select a variable resistance value which controls the output from each individual or group of switches **1062**. To accomplish strobing, the processor **1074** may be programmed to turn the switches **1062** on and off according to a pre-designated pattern dictated by the programming instructions. The processor **1074** may make use of one or more electronic timers to provide timing between on and off events. The programming instructions may provide that the switches **1062** are turned on and off according to designated sequences, thus allowing the capability of pattern generation via the processor **1074**. As mentioned before, patterns may include, for example, strobing or flashing different groups of light segments **306** (given the example of FIG. **3**) in a pre-defined (or pseudo-random) sequence, strobing or flashing different low power lamps **305** of the light segments **306** in a pre-defined (or pseudo-random) sequence, gradually dimming or brightening the light segments **306** (individually, in groups, or collectively), or various combinations of these effects.

Although the lighting frame **302** and lighting arrangement illustrated in FIG. **3** provides various advantages, other lighting frames and other lighting arrangements may also be used in a lighting effects system, and may be employed in connection with various techniques as described herein.

Another embodiment of a lighting frame **1101**, for example, is illustrated in FIG. **11**. The lighting frame **1101** shown in FIG. **11** may be used in connection with a lighting effects system **201** such as shown in and previously described with respect to FIG. **2**, and may be constructed according to general principles described previously with respect to FIGS. **15A-15C** and **16A-16E**. As shown in FIG. **11**, a lighting frame **1101** is generally ring-shaped and has an opening **1107** through which a camera or other image capture device can view. On the lighting frame **1101** may be mounted a plurality of lamps **1112** or in some instances even a single lamp **1112**. In the embodiment shown in FIG. **11**, the lamps **1112** may be embodied as slim, narrow fluorescent "cold cathode" tubes with an internal phosphorous coating emitting visible light of certain wavelength (for example, a color temperature of

around 3200 deg. K or 5500 deg. K, both of which temperatures are commonly used in film and photography applications). FIG. **14** is a graph illustrating an example of a spectral distribution of light (in terms of light wavelength) in accordance with such a lighting effects system. The lamps **1112** are preferably oriented as illustrated in FIG. **11**—that is, in a radial pattern, emanating from a centerpoint **1119** of the opening **1107** in the middle of the lighting frame **1101**. Where embodied as cold cathode tubes, the lamps **1112** may be of any suitable size, such as, e.g., 3 to 10 millimeters in diameter and 25 to 250 millimeters in length.

Preferably, the lamps **1112** are controllable such that they can produce higher intensity or lower intensity light, and/or can be turned on or off in selected groups to adjust the overall light level provided by the lighting system. One possible means for controlling the light intensity of lamps **1112** is illustrated in FIG. **13**. As shown therein, a light control system **1301** includes a selector switch **1310** which has a plurality of settings **1312**, each of the settings **1312**, in this example, providing a different combination of lamps **1112** (shown as elements **1322** in FIG. **13**). By way of illustration, a first setting may illuminate all of the lamps **1322**; a second setting may illuminate every other lamp **1322**; and a third setting may illuminate every fourth lamp **1322**, in each case providing a relatively even distribution of light but of a different overall intensity. For example, if 24 lamps were used, then the first setting would illuminate all 24 lamps, the second setting would illuminate 12 of the 24 lamps, and the third setting would illuminate six of the 24 lamps. The settings may correspond to any desired combination of lamps **1112**. For example, each setting may be designed to control an equal number of lamps **1112**, but in a different combination. The settings may be selected by any type of analog or digital input means (e.g., a manual knob, a set of switches or buttons, or a programmable interface), and any number of settings or programmable patterns may be offered.

Power for the lighting control system **1301** may be supplied by a battery **1305**, which may have a voltage rating of, e.g., 12 volts. The battery **1305** may be rechargeable in nature. Alternatively, or in addition, power may be provided from an alternating current (AC) source, such as a standard 120 volt electrical outlet, connected to an AC-to-DC power converter. The output of the battery **1305** may be controlled by a dimmer switch (not shown), to allow the light intensity level of lamps **1312** to be reduced. Alternatively, or in addition, dimming and/or pulsing can be controlled through a pulse width modulation (PWM) circuit **1317**. A first control means (e.g., a manual switch or knob, or programmable interface) (not shown) may be provided for dimming the lamps **1322**. For example, a manual knob may control the conductance of a variable resistor, thus allowing more power or less power to reach the lamps **1322**. In this way, the selected lamps **1322** may be brightened or dimmed, down to around 20% of their total light output. The PWM circuit **1317** may also, through a second control means (e.g., a manual switch or knob, or a programmable interface) allow pulsing of the light (i.e., a strobing effect) by adjustment of a pulse width modulation frequency. For example, a manual knob may control a variable resistive element, which in turn controls the width of pulses being generated by the PWM circuit **1317**. Various techniques for generating pulses of different widths using a variable resistive element to control the selection of the width are well known in the electrical arts.

Energy is preferably delivered to the various lamps **1322** in FIG. **13** through a plurality of high frequency (HF) ballasts **1325**, which are capable of converting low DC voltage of the battery **1305** to high DC voltage (e.g., 800 to 1500 volts) for

starting the lamp, and mid-level voltage (e.g., 170 to 250 volts) for sustaining lamp operation. Other techniques may also be used to deliver energy to the lamps 1322.

While shown in a radial pattern in FIG. 13, the lamps 1322 (e.g., fluorescent tubes) may also be arranged in other patterns, such as patterns similar to those depicted, for example, in FIGS. 30A, 30B and 30C. FIG. 46 illustrates one example of a pattern of arranging fluorescent tubes (in this case, circular fluorescent tubes) on a lighting frame 4602. In FIG. 46, a lighting assembly 4600 includes a ring-shaped lighting frame 4602 with two fluorescent lamps 4605, an inner (small circumference) fluorescent lamp and an outer (larger circumference) fluorescent lamp. Additional fluorescent lamps (circular or otherwise) may also be added to the lighting frame 4202, or else a single fluorescent lamp may in some cases be utilized. The lighting frame 4602 may, as previously described, be constructed of a lightweight, durable material, and it may have a bracket or other mounting mechanism for mounting to a camera frame or lens (with the camera lens preferably viewing through the generally central hole 4613 in the lighting frame 4602), and/or a bracket or other mounting mechanism for allowing the lighting frame 4602 to be connected to a yoke or stand (such as conceptually represented by arm 4619 in FIG. 46). Energy for the fluorescent lamps 4605 may be provided as previously described herein, such that the lighting assembly 4600 can provide continuous light or, if applicable, various lighting effects.

FIG. 12 is a diagram illustrating various options and accessories as may be used in connection with the lighting assembly frame depicted in FIG. 11. As shown in FIG. 12, the lighting frame 1101 may be augmented with a diffusion filter 1205 and/or a color filter 1215, which may, if desired, be secured into place through a cover 1218 (e.g., a clear plastic cover) which locks or snaps onto the lighting frame 1101. Similar accessories may be utilized, for example, in connection with the lighting frame 302 illustrated in FIGS. 3 and 4. Illustrations of filtering techniques, through the use of waveguides and other means, are described, for example, in U.S. Pat. Nos. 6,272,269 and 6,270,244, both of which are incorporated by reference herein in their entirety.

FIG. 44 illustrates, among other things, an adjustable lens cover 4418 similar in general nature to the cover 1218 shown in FIG. 12. In the particular example illustrated in FIG. 44, threading 4491 is provided on the outer surface of the lighting frame 4402 (which may be generally analogous to lighting frame 1101 shown in FIG. 12), and matching threading 4492 is provided on the interior surface of the adjustable lens cover 4418. The adjustable lens cover 4418 may be formed of clear plastic or a similar material and may be constructed with lenslike attributes (e.g., focal, diffusion) and/or may also be colorized if desired. The adjustable lens cover 4418 is secured to the lighting frame 4402 by twisting the cover 4418 onto the lighting frame 4402 in a screw-like fashion, thereby causing the threadings 4491, 4492 to interlock. By the number of rotations of the lens cover 4418 with respect to the lighting frame 4402, the distance of the "top" surface of the lens cover 4418 to the lighting elements 4405 on the lighting frame 4402 may be varied, thus allowing different lens effects. As further illustrated in FIG. 44, one or more coiled springs 4492 or other similar elements may be provided atop the lighting frame 4402, to secure one or more color gels 4415 or other filtering objects against the inner "top" surface of the adjustable lens frame 4418, when such objects are placed within the cover 4418 in the manner shown, for example, in FIG. 12.

As an alternative to the complementary threading provided on the lens cover 4418 and the lighting frame 4402, other adjustment means may be provided. For example, the lens

cover 4418 may be secured to the lighting frame 4402 by one or more adjustable screws which dictate the distance of the "top" surface of the lens cover 4418 from the lighting frame 4402. Also, slide-and-lock mechanisms may be used as well.

It will be appreciated that, in various embodiments, a flexible, lightweight and functional lighting effects system is provided, whereby relatively uniform light may be used in illumination of a subject or area. The lighting effects system may, in various embodiments, allow a lighting frame to be secured to a camera or other image capture device, so as to permit the lighting system to be mobile and move in tandem with the camera or other image capture device, if desired. Also, in various embodiments, the lighting effects system may provide a variety of lighting patterns, including programmable patterns by which individual or groups of lights can be controlled for different lighting effects. The lighting frame may, in certain instances, be formed in multiple sections and hinged to allow the lighting frame to fold, or else snapped apart section by section, for ease of transport.

In various alternative embodiments, the lighting frame need not be ring-shaped in nature, as shown in FIGS. 3 and 4, for example, but could have other shapes as well. For example, the lighting frame may be square, hexagonal, octagonal, or other polygonal, or could, for instance, have a partially polygonal shape. Preferably, the lighting frame is relatively thin, as compared to its overall size, although it need not be. Also, the lighting frame preferably has a hole generally centered therein to allow a camera or other image capture device to view through the frame, although in some embodiments a viewing hole may not be present. The exterior portion of the lighting frame, or at least the exterior portion thereof, is preferably made of a lightweight, durable material such as plastic and/or lightweight metal (e.g., aluminum), optionally anodized, although in various embodiments it can be made of other materials as well, including any type of metal, wood, plastic, or combination thereof. The interior lighting frame portion may advantageously comprise a printed circuit board.

Other variations may pertain to the manner of attaching the lighting frame to a camera or other image capture device. Rather than using a single mounting bracket or assembly, for example, multiple mounting brackets or assemblies may be used. Also, the mounting bracket or assembly may be permanently attached or affixed to the lighting frame, and may be, for example, retractable or foldable for convenience of transportation. The lighting frame may attach either to the camera body or to the lens portion of the camera. The lighting frame may attach to the camera lens through any of a variety of means, such as by engaging an outer camera lens threading through a threading on the interior circular hole of the lighting frame, engaging an inner camera lens threading by providing a complementary threaded extension for that purpose, by a strap means to secure the lighting frame to the camera and/or stand, or by a "hose-clamp" type strap which grips the outer cylinder of the camera lens. Also, rather than attaching to the camera, the lighting frame may be portable, and may be outfitted with handles for lighting crew to manually carry or hold the lighting frame, or may be adapted to attach to a stand or fixture for providing stationary illumination. The lighting frame may also be adapted to attach to a machine arm or other contrivance for allowing the lighting effects system to be moved as needed for filming or other desired purposes.

Further embodiments, variations, and modifications pertain to the type of lamp elements that may be utilized in a lighting effects system and/or the manner of constructing a lighting frame particularly well suited for placing numerous lamp elements thereon. One method of construction involves

25

the use of surface mount LEDs of the type illustrated, for example, in FIG. 31. As shown therein, a surface mount LED 3100 comprises a body 3104 having a thermal shoe on the bottom surface 3103 and a pair of soldering tabs 3102 for securing the surface mount LED 3100 to a circuit board (e.g., an aluminum core circuit board) or other suitable surface. A lens 3101 atop the body 3104 directs the light generated by the surface mount LED 3100 outwards. While the body 3104 and the lens 3101 of the surface mount LED 3100 radiate heat, the soldering tabs 3102 as well as the thermal shoe on the bottom surface 3103 assist in conducting heat to the mounting surface (e.g., circuit board) and thus may provide advantageous heat dissipation capabilities, particularly as compared to non-surface mount LEDs which tend to dissipate heat typically through their leads. Use of surface mount LEDs provides a larger and more direct heat conduction path to the mounting surface (e.g., circuit board), and may also provide advantages in ease of fabrication and improved durability.

In various embodiments as described herein, the lamp elements used in a lighting effects system or lighting apparatus may comprise high output semiconductor lights such as, for example, high output LEDs. Such high output LEDs are available from Lumileds Lighting, LLC of San Jose, Calif. under the product brand name Luxeon™. High output LEDs are presently available in white as well as colors such as green, blue, red, amber, and cyan, are fully dimmable, and generally operate at about one to several Watts (e.g., 5 Watts), outputting in certain devices approximately 24 lumens per Watt. The high output LEDs may be mounted upon, e.g., a metal printed circuit board (PCB) such as an aluminum core circuit board. High output LEDs may be used in connection with any of the embodiments previously described herein, and may provide advantages of increased lighting output with fewer lamp elements and, hence, reduced cost of construction in certain cases. However, the driving circuitry for the high output LEDs would generally need to have a higher output rating than the circuitry used for lower power LEDs.

FIGS. 36A and 36B are diagrams of two other types of high output surface-mount LEDs, both of which are commercially available from Lumileds Lighting, LLC under the brand name Luxeon™. In FIG. 36A, the surface mount LED 3600 comprises an aluminum bottom plate 3611 atop of which is a printed circuit board (PCB) 3608 (e.g., a fiberglass board such as a standard FR4 board). A high output light source 3605 is mounted atop the PCB 3608. The aluminum bottom plate 3611 acts as a thermal conveyance which assists in conduction of heat to a mounting surface (e.g., circuit board) for thermal dissipation. FIG. 36C shows an oblique view of the surface mount LED 3600 shown in FIG. 36A, illustrating, in this example, the relatively wide bottom plate 3611 relative to the size of the light source 3605. The bottom plate 3611 and PCB 3608 preferably have notches 3615 through which screws may be placed to secure the surface mount LED 3600 to a mounting surface. FIG. 36B illustrates another surface mount LED 3650 that is similar in certain respects to the surface mount LED 3600 shown in FIG. 36A, with an aluminum bottom plate 3661 and printed circuit board 3658 (e.g., fiberglass board such as a standard FR4 board). However, in contrast to the surface mount LED 3600 shown in FIG. 36A, which is Lambertian (domed) in nature, the high output light source 3655 of surface mount LED 3650 is a side emitting light source. Other alternative types of surface mount LEDs, with similar or alternative mounting mechanisms, may also be utilized in various embodiments described herein.

FIG. 37A is a diagram of one embodiment of a lens cap 3702 for a single LED. The lens cap 3702 may act as a focusing lens to direct the light output from an LED in a

26

forward (or other) direction. FIGS. 37B and 37C illustrate placement of the lens cap 3702 with respect to the surface mount LED 3600 of FIG. 36A. As illustrated, the protruding tabs 3704 on the base of the lens cap 3702 may be used to lock the lens cap 3702 into place by snugly residing in the holes 3615 of the base of the surface mount LED 3600. A similar type of lens cap may be used for other types of LEDs. While six tabs 3704 are shown in the example of FIGS. 37A-37C, the number of tabs, or the nature and/or shape of other alternative securing means, may depend upon the particular size, shape, and configuration of the LED base. Also, fewer tabs may be used if there is a desire leave some holes 3615 in the LED base available for receiving securing screws to hold the LED to a mounting surface. In such a case, the lens cap 3702 may be indented or otherwise shaped to allow relatively convenient access to the holes 3615 needed for attaching screws. The lens cap 3702 is illustrated as domed, but may be of any suitable shape for focusing light in a desired manner.

The lens cap 3702 may have an advantage in providing local effects on an individual basis for LEDs. Also, where different color lighting elements are placed within a single high output LED 3600, the lens cap 3702 may be configured to provide local blending of the different colors according to a desired mix.

FIGS. 37D and 37E are diagrams illustrating another embodiment of a lens cap 3752 for an LED, and placement thereof with respect to a particular type of LED 3600. With reference first to FIG. 37E, an illustrated embodiment of lens cap 3752 is shown from an oblique viewpoint in a generally funnel shape, with a cone-like or tapered portion 3753 and a short cylindrical portion 3754 at the apex (i.e., narrow end) of the tapered portion 3753. The lens cap 3752, including the cone-like tapered portion 3753, is preferably transmissive in nature such that light travels through it substantially unimpeded. FIG. 37D, which is a side profile diagram, illustrates preferred placement of the lens cap 3752 with respect to a particular type of LED (that is, the LED 3600 illustrated in FIGS. 36A and 36C). The cylindrical portion 3754 of the lens cap 3752 rests atop the LED 3600, with the tapered portion 3753 gradually widening away from the LED 3600. A concave recess 3755 within the cylindrical portion 3754 may be provided, and is adapted to receive the curved lens 3605 of the LED 3600, as illustrated in FIG. 36D. Light from the LED 3600 enters through the short cylindrical portion 3754 of the lens cap 3752, and exits through the top surface 3759 (see FIG. 37E) thereof. The particular shape of the lens cap 3752 in FIGS. 37D and 37E serves to collect light from the LED 3600 that would otherwise emanate omnidirectionally, and focus the light in a generally conical beam emanating from the top of the lens cap 3752, thus providing a light source with greater directivity.

The lens cap 3752 may be formed of, e.g., glass, plastic, or other suitable material or compound/layers of material, with any desired refractive index(es). One type of lens cap is commercially available, for example, from Lumileds Lighting, LLC.

FIG. 32 is a generalized diagram of an array of surface mount LEDs 3202 (of the type such as shown, for example, in FIG. 31, 36A, or 36B) mounted atop a circuit board 3204, as may be used in various embodiments as described herein (for example, the lighting effects system illustrated in FIG. 4). The circuit board 3204 may comprise rigid fiberglass or phenolic planes with electrically conductive tracks etched on them, and/or may be metallic in nature (such as aluminum core PCBs). The term "circuit board" as used herein is meant to encompass the foregoing structures as well as various other types mounting apparatus, including flexible electrical inter-

connects such as conductive membranes made on thin Mylar, silicone, or other similar materials. The surface mount LEDs **3202** may be connected together in series and/or in parallel by electrical traces **3203** on the circuit board **3200**. While the LEDs **3202** are illustrated in FIG. **32** as being in a straight line array, other LED patterns may also be utilized. As previously mentioned, the soldering tabs and thermal shoe on the bottom each of the surface mount LEDs **3202** generally assist in conducting heat to the circuit board **3204**, thus providing advantageous heat dissipation capabilities.

FIG. **35** is a diagram of a lighting apparatus **3500** embodied as a panel **3502** having lighting arrays mounted thereon or therewith, in accordance with various embodiments as described herein. As illustrated in FIG. **35**, the lighting apparatus **3500** comprises a panel **3502** which is preferably flat and provides suitable surface area for mounting a set of lamp elements, such as lamp elements **3505** on circuit board assemblies **3506**. The circuit board assemblies **3506** may generally be constructed in accordance with the principles described with respect to FIG. **32** above, and the lamp elements **3505** may comprise, for example, surface mount LEDs such as illustrated in FIG. **31**. In the example shown, the lamp elements **3505** are generally arranged in series in a straight array formation, but the lamp elements **3505** may be arranged in other patterns as well. Likewise, the circuit board assemblies **3606** are illustrated in FIG. **35** as being arranged in a symmetrical pattern of rows thus providing relatively even illumination in many scenarios, the circuit board assemblies **360** may be arranged in other symmetrical or non-symmetrical patterns, and may be grouped or clustered as well. Furthermore, while the panel **3202** is shown in FIG. **35** as being generally rectangular in shape, the panel **3202** may take any suitable shape, including, for example, hexagonal, octagonal, or other polygonal or semi-polygonal, or round, oval, or ring-shaped (such as illustrated in FIG. **4** for example).

Surface mount technology for the LEDs used in various embodiments as disclosed herein may simplify replacement of the LEDs (allowing "drop in" replacements for example) or else may allow easy replacement of an entire row or array of LEDs should it be desired to change the color of a particular group of LEDs. Also, the LED arrays may be constructed such that the LEDs have screw-in bases or other similar physical attachment means, such that the LEDs can be easily removed and replaced.

Various controls, power supply, and camera mounting means are not shown in FIG. **35**, but may be employed in a manner similar to the various other embodiments as described herein. It will be appreciated that the control electronics, power supply, and other electrical components may be part of the panel **3202** or else may be separate therefrom. Furthermore, the lighting apparatus described with respect to FIG. **35** may be embodied as a bi-color or other multi-color lighting system, as described with respect to, e.g., FIGS. **33** and **34**.

The lighting apparatus **3500** of FIG. **35** or other various lighting effects systems and apparatuses as described herein may include means for directing light at different angles. Such means may include, for example, pivotable light arrays which physically alter the angle of the lamp elements with respect to the frame (e.g., mounting) surface. The pivoting light arrays may be either manually controllable (via, e.g., a rotatable knob or crank) or electronically controllable through standard electronic input means (e.g., buttons or control knob). Such means may alternatively include adjustable lens elements (either individual or collective for an entire lens array or other group of lamp elements) for redirecting the illumination in a desired direction. Such means may further alternatively include, for example, groups of lamp elements

wherein each group has a predetermined angle or range of angles with respect to the frame surface. Each group of lamp elements may be separately controllable, so that different groups can be separately activated or de-activated, or separately intensified or dimmed. With the ability to vary the angle of the lamp elements, the lighting effects system may, for example, allow the abrupt or gradual switching from one angle of illumination to another, or from a more targeted to a more dispersive illumination pattern (or vice versa).

FIGS. **39** and **40** illustrate various panel light embodiments using surface mount LEDs. In FIG. **39**, a panel light **3900** comprises one or more rows or arrays (in this example, two rows or arrays) of surface mount LEDs **3905** secured to a mounting surface **3902**. Screws **3996** are used in this example to secure the bases of the surface mount LEDs **3905** to the mounting surface **3902**. FIG. **40** is similar, with a panel light **4001** having, in this example, four rows or arrays of surface mount LEDs **4005** securing to a mounting surface **4002** with, e.g., screws **4096**. The mounting surfaces **3902** or **4002** may comprise a circuit board, and thus LEDs **3905** or **4005** may be mounted directly to a circuit board type mounting surface. The circuit board may be attached to an outer frame of aluminum or another preferably lightweight material, to provide a solid structural support for the circuit board. Panel lights **3900** or **4001** such as shown in FIGS. **39** and **40** may be used as relatively lightweight, portable lighting fixtures that generate less heat than incandescent lighting fixtures, and may be provided with handles for manual manipulation or with brackets or other means to connect to a yoke, stand, or other mechanical contraption. The panel lights **3900** and **4001** may use a ballast to supply power or, in some instances, may be directly connected to an AC electrical outlet (e.g., wall socket).

FIG. **41A** illustrates a panel light **4100** of the general type shown, for example, in FIGS. **39** and **40**, further illustrating a number of heat conductive fins **4112** which serve to assist with heat dissipation. The panel light **4100** may optionally include a means for facilitating attachment to a single- or multi-panel lighting assembly. In the present example, the panel light **4100** has a pair of T-shaped cutouts **4116** located in each of the fins **4112**, such that the T-shaped cutouts **4116** form a pair of straight line, T-shaped grooves through the series of fins **4112**. The T-shaped cutouts **4116** may be slid over a T-shaped bar to attach the panel light **4100** to a lighting assembly.

FIG. **41B** is a diagram of an example of a multi-panel lighting assembly **4150**, illustrating attachment of a panel light **4100** as shown in FIG. **41A** to the lighting assembly **4150**. In the example of FIG. **41B**, the lighting assembly **4150** includes a pair of T-shaped bars **4165** which protrude from a lighting assembly frame **4160**, and which are matched to the T-shaped cutouts **4116** in the lighting panel **4100** of FIG. **41A**. Once the lighting panel **4100** is slid into place along the T-shaped bars **4165**, they securely hold the lighting panel **4100** in place. Insulated caps (not shown), made of rubber or plastic for example, or other such means may be placed on the ends of the T-shaped bars **4165** to prevent the lighting panel **4100** from sliding out of place. In the particular example shown, the multi-panel lighting assembly **4150** is configured to receive up to two lighting panels **4100** of the type shown in FIG. **41A**, although such an assembly may be configured to receive any number of lighting panels **4100** depending upon the particular needs of the application. The multi-panel lighting assembly **4150** also has another lighting panel **4167** that may be "permanently" attached to or integral with the multi-panel lighting assembly **4150**, or else may likewise be attachable and detachable in the manner of lighting panel **4100**. The

multi-panel lighting assembly **4150** thereby provides a lighting operator with a variety of lighting configurations in a single unit. Other similar modular multi-panel lighting assemblies may be constructed according to the same or similar principles, having any number of panel lights in a variety of different sizes and/or shapes. The multi-panel lighting assembly **4150** may, in certain embodiments, be used in connection with a lighting stand such as illustrated, for example, in FIG. **43** and described elsewhere herein.

Attachment of panel lights (such as, e.g., panel lights **4100**) to a multi-panel lighting assembly (such as, e.g., multi-panel lighting assembly **4150**) may be accomplished by a variety of means. For example, rather than using complementary bars **4165** and cutouts **4116**, the panel light **4100** may drop down and lock into an opening in the multi-panel lighting assembly **4150**. In such a case, the housing or frame of the multi-panel lighting assembly **4150** may have a molded beam with traverses the outer edge of the opening in which the panel light **4100** would be positioned. Locking tabs, for example, or other such means may be used to secure the dropped-in panel light **4100** within the opening if the multi-panel lighting assembly **4150**.

FIG. **38A** is a diagram of ring-shaped lighting panel **3800** having surface mount LEDs **3805** (such as, e.g., the high output surface mount LEDs shown in FIG. **36A** or **36B**) attached to a mounting surface of a frame **3802** which, as with the panel lights described before, may comprise a circuit board. The ring-shaped lighting panel **3800** may have a camera mounting bracket (not shown in FIG. **38A**) and generally be utilized in a manner similar to the ring-shaped lighting assembly shown in FIG. **4** and described in various places herein. The surface mount LEDs **3805** in the example of FIG. **38A** are arranged in a plurality of rows or arrays **3806** emanating from the center of the hole or cutout region **3803** of the lighting panel **3800**. While a relatively dense pattern of LEDs **3805** is illustrated in FIG. **38A**, the pattern may be less dense, and the LEDs **3805** need not necessarily be deployed in rows or arrays. Because the LEDs **1305** in this example are high output, the lighting panel **3800** outputs a greater total amount of light than with ordinary LEDs. Also, fewer LEDs need to be physically mounted on the lighting panel **3800**, which can reduce cost of construction.

FIG. **38B** is a cross-sectional view of the lighting panel **3800** showing the inclusion of optional fins **3812** on the backside of the frame **3802**, to assist with heat dissipation. The fins **3812** are shown in cross-section, and form a set of parallel members similar to the fins **4112** shown in FIG. **41A**.

FIG. **42A** illustrates an integrated lens cover **4200** which can be placed atop, e.g., a panel light **4202** for providing focusing for a plurality of LEDs simultaneously. The panel light **4202** has rows of LEDs **4205**, similar to FIGS. **39** and **40**, and the integrated lens cover **4210** may be placed atop the panel light **4202** and, e.g., snapped into place by tabs **4212**, or otherwise secured to the frame of the panel light **4202**. FIG. **42B** shows additional detail of the integrated lens cover **4210**. The integrated lens cover may be formed of any suitable lightweight, durable material (such as plastic) and preferably has a number of focal lens portions **4219** which, when the unit is placed atop the panel light **4202**, act as focal lenses for LEDs **4205** which are positioned directly beneath the focal lens portions **4219**. The integrated focal lens **4210** may thus allow the panel light **4202** to provide more directed, focused light (e.g., in a forward direction), rather than allowing the light to diffuse in an omnidirectional fashion. Alternatively, the integrated focal lens **4210** may provide other focusing effects that can be done with lenses. The focal lens portions

4219 may be domed or semi-domed, or else any other shape sufficient to serve their intended purpose.

FIGS. **42C** and **42D** are side profile diagrams illustrating further details of alternative embodiments of an integrated focal lens. FIG. **42C** illustrates an integrated focal lens **4265** with tapered focal lenses **4251** emanating from the underside of the sheet-like surface **4250** of the integrated focal lens **4265**. In the instant example, the tapered focal lenses **4251** appear as inverted cone-like projections, with small concave recesses **4252** for receiving the dome-like lenses **4255** of LEDs **4256**, which are mounted to a mounting surface **4260**. The tapered focal lenses **4251** may be constructed in a manner as generally described previously with respect to FIGS. **37D** and **37E**, and may also have a short cylindrical portion **3754** such as illustrated in those figures, for resting atop the LEDs **4256** and providing added support to the top surface **4250** of the integrated focal lens **4265**. Alternatively, separate struts (not shown) may be molded to the underside of the integrated focal lens **4265** to provide such support. The integrated focal lens **4265** may, in certain embodiments, be constructed by attaching (using glue or solvent) individual, tapered focal lenses of the type illustrated in FIGS. **37D** and **37E** to the underside of a clear plastic sheet, and then providing securing means for the overall resulting lens device to allow it to secure to, e.g., a panel lighting fixture.

FIG. **42D** illustrates an alternative embodiment of an integrated focal lens **4285**, with bubble-shaped or domed focal lenses **4271** on the topside of the sheet-like surface **4250** of the integrated focal lens **4285**. The focal lenses **4271** may be constructed in a manner as generally described previously with respect to FIGS. **37A-37C**, and may also have one or more projecting members or struts (not shown) on the underside of the integrated focal lens **4285** to provide support for the top surface **4270** thereof. Other shapes and styles of integrated focal lenses (or other lenses) may also be utilized for an integrated focal lens.

FIG. **43** illustrates a panel lighting assembly **4300** in which a panel light frame **4302** is attached to a stand **4380**. The panel light frame **4302** may include multiple panel light sections **4303**, **4304**, or may be a single unitary panel light. The stand **4380** may be of a conventional nature, with a C-shaped yoke **4381** for securing the panel light frame **4302** crossbar and allowing it to tilt for directional lighting. A twisting handle **4317** may be used to lock the panel light frame **4302** at a particular tilting angle. The C-shaped yoke **4381** may be rotatable or pivotable by placement atop a fluid head **4382**, which in turn is positioned atop a stem **4384** and tripod **4386**. The panel lighting assembly **4300** thus conveniently provides a variety of directional lighting options for the panel light frame **4302**.

In alternative embodiments, a ball-and-socket mechanism may be used to rotate/pivot an attached lighting panel, using socket joints similar to those used for, e.g., computer monitors. Likewise, in any of the foregoing embodiments, motorization may be employed to control the movement of the lighting yokes or stands. Motorized control is well known in the art for lighting apparatus (particularly in the performing arts field), and the motorized control may be either automated or manual in nature.

FIG. **45** is a diagram of another embodiment of a lighting fixture **4500** employing semiconductor light elements. In FIG. **45** is shown a flexible strip **4502** with an array of surface mount LEDs **4505** mounted on the flexible strip **4502**. The flexible strip **4502** preferably comprises a circuit board that may be comprised, for example, of a material such as mylar or composite material, of sufficient thinness to allow the circuit board to be bent and/or twisted. The circuit board may be at

31

least partially encased in an insulated (e.g., rubberized) material or housing that is likewise flexible and thin. Heat dissipating fins (not shown in FIG. 45) may protrude from the backside of the flexible strip 4502, to assist with cooling of the surface mount LEDs 4505. While a single array of surface mount LEDs 4505 is illustrated in the example of FIG. 45, two or more arrays of LEDs 4505 may be used, and may be positioned, e.g., side by side. An electrical connector 4540 with electrical contact receptacles 4541 is also illustrated in the example of FIG. 45, for receiving an electrical cord (not shown) supplying power for the LEDs 4505. Other alternative means for providing electrical power, such as a battery located in an integrated battery housing, may also be used.

According to one or more embodiments as disclosed herein, a versatile lighting apparatus in the form of an LED-based light panel is provided, preferably having a variety of mounting options or configurations, an attachable or integrated battery unit, and alternative means for receiving a power supply input. In a preferred embodiment, the versatile LED-based light panel includes a panel frame, and a plurality of LEDs or other light elements secured to the panel frame. A self-contained battery unit securably attaches to the outside of the panel frame. The light panel may have a dimmer switch, and may also be capable of receiving power from a source other than the self-contained battery unit. The lighting apparatus can be mounted to a camera or a stand through adapters. Diffusion lenses or color gels can be integrated with or detachable from the light panel. The lighting apparatus may conveniently be provided in the form of a kit, with one or more of a light panel, self-contained battery unit, compact stand, connecting cable(s), adapter(s), lenses or color gels, and so on, provided in a single package.

FIGS. 47A and 47B are diagrams of a lighting apparatus 4700 in accordance with one or more embodiments as disclosed herein. The lighting apparatus 4700 is preferably portable and versatile in nature, as further described herein. The lighting apparatus 4700 in this example includes a panel, fixture or frame (hereinafter "panel") 4702 having a plurality of semiconductor light elements (such as LEDs or LECs) 4705 mounted on a mounting surface 4704 of the panel 4702. As illustrated in FIG. 47A, the semiconductor light elements 4705 may be disposed in uniform arrays to provide a broad light source. The mounting surface 4704 may include one or more circuit board assemblies, generally constructed in accordance with the principles described previously with respect to FIG. 32. Although the semiconductor light elements 4705 are illustrated as being arranged in uniform arrays, they may be arranged in other patterns as well. Furthermore, while the panel 4702 is shown in FIG. 47A as being generally rectangular in shape, the panel 4702 may alternatively be of any suitable shape, including, for example, hexagonal, octagonal, or other polygonal or semi-polygonal, or round, oval, square, or ring-shaped (such as illustrated in FIG. 4, for example).

The semiconductor light elements 4705 may be surface mounted (e.g., surface mount LEDs), which may have the advantage, for example, of simplifying replacement of the LEDs (allowing "drop in" replacements for example) or else may allow easy replacement of an entire row (e.g., interconnect set, etc.) or array of LEDs should it be desired, for example, to change the color, size, shape, or other characteristics of a particular group of LEDs. The light elements or LEDs may have screw-in bases or other similar physical attachment means, such that the LEDs can be easily removed and replaced.

The panel 4702 may further include an integrated dimmer control 4726, in the form of a knob, switch, or other mecha-

32

nism, to allow the intensity of the semiconductor light elements 4715 to be adjusted. As one example of an implementation, a dimmer control 4726 in the form of a manual knob may control the conductance of a potentiometer or variable resistor (similar to 5735 in FIG. 57), to adjust the amount of current reaching the semiconductor light elements 4705. More than one dimmer control 4726, and/or switches, may optionally be provided, so as to control groups of semiconductor light elements 4705, for example, or to turn on or off certain groups of the semiconductor light elements 4705. An example of electronic circuitry as may be used in connection with dimmer control 4726 is described with respect to FIG. 57.

As illustrated in FIG. 47B, the panel 4702 preferably further includes a socket 4724 or other input for receiving a power connection (e.g., cable) to provide electrical power to the semiconductor light elements 4705. The panel 4702 may also include various heat dissipating fins 4712, which may be arranged, for example, in arrays of metal or heat conductive rods, integrated on the back side of the panel 4702, in order to efficiently dissipate heat generated by the semiconductor light elements 4705. The heat dissipating fins 4712 may generally be similar to those described elsewhere herein, for example, with respect to FIG. 38A or 41A. The heat dissipating fins 4712 may be of any suitable size or shape, and may be extended, for example, to accommodate higher wattage LEDs or light elements. Other types of heat dissipation mechanisms may also be used.

The lighting apparatus 4700 of FIGS. 47A and 47B may be particularly adapted to receive an attachable/detachable battery unit, so as to provide a self-contained unit having its own power source. FIGS. 48A and 48B are diagrams of a panel-based lighting apparatus 4802 such as illustrated in FIGS. 47A-B, together with an attachable battery unit 4830, to form a self-contained, self-powered lighting apparatus 4800. The battery unit 4830 may be attachable to the panel 4802 in any of a variety of manners. In the particular example shown in FIGS. 48A and 48B, the battery unit 4830 comprises a set of struts 4832 that attach to corresponding receptacles 4836 of the panel 4802. FIG. 48A shows a perspective view of the light panel 4802 and battery unit 4830 slightly separated, while FIG. 48B shows a side view of them attached to one another, with the struts 4832 inserted in the receptacles 4836 of the panel 4802. FIGS. 49A and 49B are diagrams showing attachment of the light panel 4802 to the attachable battery unit 4830. FIG. 49A in particular is a simplified diagram omitting certain details such as the heat dissipating fins.

A wide variety of alternative means may be used to attach the battery unit 4830 to the panel 4802; by way merely of example, the battery unit 4830 may slidably attach and engage with the panel 4802, or may have external tabs that grip the panel 4802, or may have pins or screws that engage with the panel 4802.

The battery unit 4830 preferably delivers power to the light panel 4802 through an electrical connector 4840, which may take the form of, e.g., a jumper cord, and may insert into electrical sockets 4834 (in the battery unit 4830) and 4824 (in the panel 4802). Alternatively, the front side of the battery unit 4830 and backside of the panel 4802 may be provided with a mating male/female electrical plug and socket, which automatically engage when the battery unit 4830 is attached to the panel 4802. As with the lighting apparatus 4700 of FIGS. 47A-B, a dimmer switch 4826 may be provided in a convenient location on the panel 4802, to adjust the light intensity. One or more batteries, possibly replaceable, may be integrated with battery unit 4830. The battery, or batteries, may have a nominal voltage rating of appropriate level, such as 12

volts. The battery, or batteries, of battery unit **4730** is/are preferably rechargeable in nature.

A diffusion lens or filter may also be used, by itself or in conjunction with a color gel or colored lens, to diffuse or soften the outgoing light. A diffusion lens or filter may be formed of, e.g., clear or white opaque plastic, and may be configured in a shape of similar dimension to the panel **4702** or **4802** to facilitate mounting thereon. One such diffusion filter **5029** is shown in FIG. **50A**. A preferred diffusion filter/lens would be a Light Shaping Diffusor material (e.g., holographic, etc.). A color correction mechanism, such as a lens filter and/or color gel, may be used to alter the color of the light elements of a lighting apparatus such as depicted in FIG. **47A-B** or **48A-B**. For example, LED light sources could, if necessary, be converted to "tungsten daylight" (similar in hue to an incandescent bulb) by use of a color gel and/or colored lens.

The lighting apparatuses **4700** and **4800** are preferably adapted to be utilized in conjunction with various lenses and/or color gels, to increase their versatility. FIG. **50A** is a diagram illustrating one embodiment having a lens **5010** and optional color gel **5029** used with the lighting apparatus **4800** illustrated in FIGS. **48A-B**, and FIG. **50B** is a side view diagram illustrating the lens **5020** in place. The lens **5010** is preferably readily attachable to the panel **4802** of the lighting apparatus **4800**, by fastening means such as complementary Velcro patches **5022**, **5012**. Alternatively, the lens **5010** could snap or slide on to the panel **4802**, or be attached using screws, nuts/bolts, pins, or other such means. The filter/lens **5010** (as with **6327**, described later herein) may comprise, e.g., a Fresnel lens, a holographic lens, or any other type of lens, or combinations thereof. The color gel **5029** is preferably inserted beneath the lens **5010** and is secured beneath it. As depicted in FIG. **50A**, the color gel **5029** has cutouts on each of the corners so as not to interfere with the Velcro patches **5022**, **5012**.

The lighting apparatus **4700** is preferably portable in nature and can be adapted for use in a variety of ways. To facilitate mounting of the lighting apparatus **4700** (whether or not attached to a battery unit, as depicted in FIGS. **48A-B**), the lighting apparatus **4700** may be provided with one or more adapters. FIG. **59** is a diagram illustrating an example of a lighting apparatus **4700** in the form of a panel **4702** with one or more adapters **5906**, **5907** for mounting or affixing the panel **4702** to a camera, stand, or other object or surface. In the example depicted in FIG. **59**, the adapters **5906**, **5907** are in the form of receptacles suitable for receiving a mechanical pin (or a similar fastener such as a screw or bolt), allowing convenient and rapid deployment of the lighting apparatus **4700** on, e.g., a camera or stand. Other adapters or fastening means (e.g., hinged tabs, sliding/coupling members, etc.) may also be used.

Examples of ways in which the light apparatus **4700** can be mounted on a camera, stand or other object or surface are illustrated in FIGS. **51** through **55**, and **60** through **63B**. For example, the lighting apparatus **4700** may be mounted to a camera, directly to the camera housing or to an arm attached to the camera housing. FIG. **51** is a diagram showing one possible mechanism for mounting a lighting apparatus **4700** in the form of a light panel to a camera **5107**. While the description below is explained in terms of lighting apparatus **4700**, it also applies to the lighting apparatus **4800** having an attachable battery unit, as well as other possible lighting apparatuses as well. In FIG. **51**, the camera **5107** includes or is configured with an attachment arm **5110** which may be used for mounting the lighting apparatus **4700**. The attachment arm **5110** may, for example, be an articulated arm sys-

tem of the type commercially available from, e.g., Noga of Israel, sold under the trade name "Hold-It." The attachment arm **5110** comprises a ball joint **5120** attached to the housing (or shoe) of the camera **5107**, a second ball joint **5125** attached to the lighting apparatus **4700** (via, e.g., an adapter **5906** such as shown in FIG. **59**), and a pair of arms **5121**, **5124** meeting at an adjustable knob interface **5129**. A camera shoe is a standard fitting on a camera that attaches accessories; a hot shoe is a receptacle on a camera housing that provides an electrical signal to an external accessory such as a flash unit. The knob **5129** in this particular example allows the ball joints **5120**, **5125** to loosen so that the arms **5121**, **5124** can be positioned as desired, and again tightened with the knob **5129**. In this example, the lighting apparatus **4700** preferably includes a pin receptacle for receiving a threaded pin from the ball joint **5125** of the attachment arm **5110**.

FIGS. **52A** through **52C** are diagrams illustrating other attachment options, using various mounting pins, in connection with the lighting apparatus **4700** of FIGS. **47A-B**. FIG. **52A**, for example, illustrates a mounting pin **5210** that may be used to allow the lighting apparatus **4700** to attach to a stand or tripod. The mounting pin **5210** in this example includes a threaded pin **5219**, a cylindrical body **5212**, and a grooved depression **5223** for providing a gripping region for a clamp or other attachment mechanism. The lighting apparatus includes a threaded receptacle (of the type shown in, e.g., FIG. **59**, as adapter **5906**) for receiving the threaded pin **5219**. FIG. **55** depicts the lighting apparatus **4700** attached to a stand **5500** using a mounting pin such as **5210**. The stand **5500** has a base **5512**, a main arm **5512** (possibly telescoping in nature), and an adjustable swing arm **5519** connected to a clamp member **5514**. The clamp member **5524** in this example comprises a knob **5525** which loosens and tightens two opposing plates that grip the mounting pin **5210** between them. Alternatively, or in addition, the lighting apparatus **4700** may have a threaded receptacle on its shorter side instead of, or in addition to, a threaded receptacle on its longer side, to provide an alternative mounting option.

FIG. **52C** illustrates attachment of the lighting apparatus **4700** to a mounting pin **5210** similar to that shown in FIG. **52A**, but in this instance being coupled to an adapter on the narrow side of the lighting apparatus **4700** instead of its long side (i.e., using an adapter **5907** such as shown in FIG. **59**).

In FIG. **52B**, the lighting apparatus **4700** is attached to a stand or camera using a mounting pin **5250**. The mounting pin **5250** in this example also includes a threaded pin **5269** and a cylindrical body **5262**. In this case, the mounting pin **5250** may have a T-bar **5259** that is securably attached to the cylindrical body **5262**, or else fits into a hollow receptacle to secure it to the cylindrical body **5262** of the mounting pin **5250**, thereby allowing it to slide onto a camera having curved fins or other members for receiving the wings of the T-bar **5259**. The mounting pin **5250** may alternatively have a pin, receptacle, or other member for mounting into a camera shoe or a stand, thus securing the lighting apparatus **4700** to the camera or stand.

The lighting apparatuses **4700** or **4800** may also be adapted to be placed on a compact stand. FIGS. **53A** through **53D** are diagrams showing different views of the lighting apparatus **4800** mounted on one possible type of stand **5310**. In this example, the stand **5310** comprises a base plate **5320** with mounting arms **5325**, one on each side, attached to L-shaped struts on the base plate **5320**. The mounting arms **5325** preferably allow the lighting apparatus **4800** (comprised of the panel **4802** and battery unit **4830** in this example, although the same principles would apply to a lighting apparatus **4700** having only a panel **4702**) to tilt forward and backward, thus

35

allowing rapid adjustment of the angle of light provided. The stand 5310 is preferably of sufficient weight or bulk to keep the entire unit stable, and to prevent it from falling over regardless of the angle of tilt.

FIG. 54 is a diagram showing details of one possible mounting arm 5325 configuration for the stand 5310 illustrated in FIGS. 53A-D. As shown in FIG. 54, the mounting arm 5320 is attached to the top of the L-shaped strut 5410 of the base plate, and includes a rotatable rod 5415 having a pin 5421 mounted on a base 5419 attached to the rotatable rod 5415. The pin 5421 in this example includes a spring-loaded ball bearing 5424. The lighting apparatus 4700 or 4800 preferably has a pin receptacle complementary to the pin 5421 with ball bearing 5425, on each side of the base plate, allowing the lighting apparatus 4700 or 4800 to be slid down the pin(s) 5421, with the spring-loaded ball bearings 5424 allowing the pins 5421 to lock into place within the pin receptacles. The lighting apparatus 4700 or 4800 can be removed by pulling it firmly while holding the base plate 5320 in place. Of course, other attachment means can be used to allow the lighting apparatus 4700 or 4800 to be attached to a stand, including mounting pins, screws, nuts/bolts, sliding tabs, snapping fasteners, and so on.

The lighting apparatuses 4700 or 4800 in certain embodiments may also be stackable to allow convenient expansion of the lighting source area. FIG. 62 illustrates an example of a stackable panel light 6200, shown mounted on a stand 6220 (similar to stand 5320 of FIGS. 53A-D). In FIG. 62, two panel-type lighting apparatuses 4700 are vertically stacked, being held together by one or more front brackets 6205, 6206 and/or one or more side brackets 6225, which can conveniently be secured to adapters of the type shown in FIG. 59 (i.e., adapters 5906, 5907) using pins or screws 6226. In the example of FIG. 62, a side bracket is only placed on one side because of the presence of dimmer switches on the opposite side. The front bracket(s) 6205, 6206 may be placed anywhere along the border between the two lighting apparatuses 4700 so long as they sufficiently secure them together (for example, a single bracket may be centered). Also the brackets may be placed on the backside rather than the front. In any of the embodiments using stacked light panels, power may be provided to both of the lighting apparatuses 4700 using, for example, a split cable or Y-cable that emanates from a single power source.

The lighting apparatuses 4700 or 4800 may also be adapted to be placed on a tripod type stand. FIGS. 60 and 61 are diagrams showing different types of tripod configurations. In FIG. 60, the lighting apparatus 4700 is placed on a compact tripod stand 6013 having a ball joint 6016 allowing flexible tilting and angling of the lighting apparatus 4700. In FIG. 61, a tripod 6113 supports an arm (in this example, a telescoping arm 6122) which in turn supports a ball joint 6116 similar to that of FIG. 60, thereby allowing flexible tilting and angling of the lighting apparatus 4700.

FIGS. 63A and 63B are diagrams illustrating another embodiment of a camera-mountable lighting apparatus 6310. In FIG. 63A-B, the camera-mountable lighting apparatus 6310 includes a lighting frame or housing 6302 in the general nature of a panel light, and is attachable to a camera 6307 using, e.g., a mounting bracket 6355. The lighting apparatus 6310 may include a number of semiconductor light elements 6305 arranged in a suitable pattern on a front mounting surface of the panel 6302. The panel 6302 may, as described previously, be configured with heat dissipating fins 6312 to allow cooling of the light elements 6305 and any other resident electronics. A dimmer switch 6326 having functionality as previously described herein may optionally be provided. A

36

lens cover 6328, of the type generally described with respect to FIGS. 42A through 42D, may be placed in front of the light elements 6305. The lens cover 6328 may be comprised of individual lenses 6327, as illustrated in FIG. 63B, of a type similar to that described with respect to FIG. 43C (i.e., generally conical in shape). The lenses 6327 may be a focusing lens, such as a Fresnel lens, and may be positioned so as to abut one another, thereby providing a more contiguous light source as generated from the various light elements 6305.

The mounting bracket 6355 may be hinged to allow the panel 6302 to tilt backward or forward, and may also allow the panel 6302 to swivel right or left. A mounting pin 6371 may be provided to allow it to affix to the camera 6355, or else a T-bar may be used similar to that shown in FIG. 52B.

A lighting apparatus may conveniently be packaged in the form of a kit that includes a number of components providing increased convenience, flexibility, and adaptability to operators in the field. For example, a lighting apparatus kit may include one or more lighting panels 4702, as well as one or more battery units 4830 (and/or battery adapters such as described with respect to FIG. 58), power jumper cable (for connecting the power between the panel(s) 4702 and battery unit(s) 4830), an AC adapter and power/recharging cable, one or more lenses 5010, a set of colored or diffusion gels 5029 of various tints and hues, or providing light shaping or diffusion (such as with a Fresnel lens or holographic lens), and/or one or more compact mounting stands 5310 (or other accessories described herein), all of which can be packaged conveniently in a portable case. The colored or diffusion gels 5029 may be integrated with the panel 4802, or else detachable as depicted in the example of FIGS. 50A-B.

The lighting apparatus and/or battery unit may have electronics which also provide increased performance, versatility, and/or flexibility. FIG. 56 is a simplified block diagram illustrating, for example, components of one possible embodiment of a battery unit 5600, which may be physically constructed in accordance with the battery unit 4830 of FIGS. 48A-B or otherwise. The battery unit 5600 illustrated in FIG. 56 includes a recharging circuit 5615 in addition to one or more batteries 5609. A socket 5619 is provided for either receiving an output electrical connector 5612 intended to be connected to a light panel (e.g., 4802), or an input electrical connector 5626 which provides a DC voltage source. In the latter case, the input electrical connector 5626 may be connected to a wall source via, e.g., an AC-to-DC adapter. The battery or batteries 5609 may be of any suitable type, for example, Lithium-ion, Nickel-metal-hydride (NIMH), Nickel-cadmium, or any other suitable type. The kit may also include a DC-to-DC adapter to provide a more suitable voltage (e.g., 7.2 V to 12V, which may be attached between the camera and its battery).

The battery unit 5600 may optionally include one or more LED indicators for indicating the state of charging (e.g., when the battery or batteries 5609 is/are being recharged), and/or act as a meter to indicate the remaining battery charge. For example, the battery unit 5600 may have five LED indicators—two green (e.g., full or almost full), one amber (e.g., warning), and two red (e.g., approaching empty and virtually empty), to indicate the amount of remaining battery charge as it gradually depletes.

FIG. 57 is a functional block diagram illustrating an example of circuits or components of an LED-based light panel 5700, as may be constructed in accordance with, e.g., light panel 4702 or 4802 described elsewhere herein. The LED-based light panel 5700 in this example includes a power regulator 5710 which preferably provides a relatively constant or stabilized current output to one or more arrays of

series of LEDs **5740** (or other semiconductor light elements). Details of possible embodiments of a power regulator **5710** are described in copending U.S. application Ser. No. 10/708,717 filed Mar. 19, 2004, entitled "Omni-Voltage Direct Current Power Supply," hereby incorporated by reference as if set forth fully herein. The power regulator **5710** preferably includes a switched power supply **5720** under control of a control circuit **5725**, such as a PIC microcontroller **5725**. The switched power supply **5720** may be a buck/boost power supply, or else simply a buck or boost power supply, or other type of power supply. A buck/boost power supply allows the most flexibility, in that the input voltage could vary over a relatively wide range; a particular example is described in application Ser. No. 10/708,717 referred to above. A voltage sense circuit **5731** and current sense circuit **5732** provide feedback information to the PIC microcontroller **5725**, which information is used in maintaining the output current to the LEDs **5740** at a stable level, and thereby reducing undesirable artifacts such as flicker.

In FIG. **57**, a dimmer switch **5726** adjusts a potentiometer or variable resistor **5735**, which in turn provides a dimming control input signal **5737** to the power regulator **5710**. In a preferred embodiment, the dimmer control input signal **5737** adjusts the level of gain in a feedback loop for the PIC microcontroller **5725**, thus allowing adjustment of the amount of output current for the LEDs **5740**. The circuitry of FIG. **57** can allow, for example, the adjustment of light intensity without a substantial change in the output color temperature of the light source (i.e., the LEDs), and again, without flicker even at relatively low light output levels. These can be significant advantages to those working in the field.

The battery unit **4830** described previously herein may take on various different forms and configurations. In alternative embodiments, for example, the battery unit **4830** may, for example, comprise one or more "standard" or conventional camera batteries, as may be obtained by companies such as, e.g., Sony, Panasonic, Canon, and the like. FIG. **58** is a diagram of an embodiment of a battery unit **5800**, including an adapter panel **5830** for receiving at least one attachable battery **5850**, such as a DV ("digital video") battery. A DV type battery typically has a battery casing designed to be snapped directly into the camera, although DV batteries may differ from camera manufacturer to manufacturer. The adapter panel **5830** is preferably constructed to mate to a particular type or brand of battery, and thus different adapter panels **5830** may be made available, each suited to a particular battery or family of batteries. At least some DV batteries output less than 12 volts—for example, a typical output voltage is 7.2 volts. The battery unit **5800** may, as illustrated in FIG. **58**, comprise two receptor plates **5840** each adapted to securably attach a battery **5850** to the adapter panel **5830**. Electrical contacts **5842** provide electrical connection from the battery **5830** to downstream electronics or a power output source. The two batteries **5850** may be electrically connected in series via electronics integrated in the adapter panel **5830**, thus doubling the voltage to, e.g., 14.4 volts. Alternatively, the adapter panel **5830** could include a transformer of other type of DC-DC conversion circuitry to step up the voltage to 12 volts or some other appropriate level.

The battery unit **5800** preferably includes struts **5832** or other attachment means similar to those of battery unit **4830**, in order to allow the battery unit **5800** to readily attach to, e.g., an LED based light panel **4802**, in a manner similar to the way in which battery unit **4830** may connect to the panel **4802**.

Certain embodiments have been described with respect to the placement of lamp elements (e.g., LEDs) on a "mounting surface" or similar surface or area. It will be appreciated that

the term "mounting surface" and other such terms encompass not only flat surfaces but also contoured, tiered, or multi-level surfaces. Further, the term covers surfaces which allow the lamp elements to project light at different angles.

Various embodiments have been described as having particular utility to film and other image capture applications. However, the various embodiments may find utility in other areas as well, such as, for example, automated manufacturing, machine vision, and the like.

While preferred embodiments of the invention have been described herein, many variations are possible which remain within the concept and scope of the invention. Such variations would become clear to one of ordinary skill in the art after inspection of the specification and the drawings. The invention therefore is not to be restricted except within the spirit and scope of any appended claims.

What is claimed is:

1. An illumination system adapted for lighting a subject for film, photography or video, comprising:

a light panel having a forward-facing front mounting surface with a substantially unobstructed perimeter and a rear portion, said light panel having a plurality of semiconductor light elements disposed on said front mounting surface so as to provide continuous forward-projected illumination suitable for image capture in motion picture, film or television, and over an area wider than said light panel, said light panel comprising or attached to a frame component on the rear portion of said light panel thermally coupled to said semiconductor light elements for dissipating heat generated by said semiconductor light elements into the environment via conduction, and further comprising a securing mechanism securable to a camera apparatus whereby the light panel is readily attachable to and detachable from the camera apparatus; and

a dedicated self-contained battery unit releasably attachable to said light panel, said dedicated self-contained battery unit comprising a housing securably and rigidly attachable to said light panel and encasing a battery to form a single integrated structure when the light panel and battery unit are securably attached together, such that power from the dedicated self-contained battery unit is provided to said semiconductor light elements and is not provided to the camera apparatus.

2. The illumination system of claim 1, wherein said semiconductor light elements comprise light emitting diodes (LEDs).

3. The illumination system of claim 2, wherein said LEDs are arranged in a plurality of substantially parallel linear rows across a face of said light panel.

4. The illumination system of claim 1, further comprising:

a power adapter for providing an alternative means of electrical power to said light panel from an external power source in the absence of, or in addition to, said dedicated self-contained battery unit, and

a portable case for holding said light panel, said dedicated self-contained battery unit, and said power adapter.

5. The illumination system of claim 4, wherein said light panel comprises a dimmer switch and a power regulator for providing a constant direct current to said semiconductor light elements, said dimmer switch allowing manual adjustment of the direct current provided to said semiconductor light elements and thereby an illumination intensity of said semiconductor light elements when powered either by said dedicated self-contained battery unit or said external power source.

39

6. The illumination system of claim 4, wherein said dedicated self-contained battery unit is rechargeable via said power adapter.

7. The illumination system of claim 4, wherein said power adapter comprises an AC-to-DC power converter.

8. The illumination system of claim 4, wherein said power adapter comprises a DC-to-DC power converter.

9. The illumination system of claim 1, further comprising a releasably attachable, light permeable focusing lens cover capable of being temporarily secured to said light panel for focusing light from said semiconductor light elements.

10. The illumination system of claim 1, wherein said light panel comprises integrated electronics for providing a constant direct current to said semiconductor light elements, and wherein said integrated electronics includes a feedback path to sense the current provided to said semiconductor light elements and regulate said constant direct current.

11. The illumination system of claim 1, further comprising a second light panel independent and separate from said first light panel and a bracket for securing said first light panel and second light panel in a stacked arrangement, said second light panel having a plurality of semiconductor light elements secured thereto so as to provide continuous illumination over an area.

12. The illumination system of claim 1:

wherein said dedicated self-contained battery unit comprises a plurality of struts, and wherein said light panel comprises a plurality of receptors for receiving and locking said struts.

13. The illumination system of claim 1, further comprising one or more color filters or color filters securably attachable to said light panel, at least one color filter substantially conforming to the dimensions of said focusing lens cover, for altering the color characteristics of light from said semiconductor light elements.

14. The illumination system of claim 1, further comprising a plurality of releasably attachable focusing lens covers each having different focal properties and capable of being temporarily secured to said light panel for focusing light from said semiconductor light elements.

15. The illumination system of claim 1, wherein said semiconductor light elements comprise high output light emitting diodes (LEDs).

16. The illumination system of claim 15, wherein said high output LEDs have a power rating of about 1 Watt or more.

17. The illumination system of claim 1, further comprising an articulated arm supporting said light panel, whereby said light panel tilts or pivots such that an angle of illumination from said semiconductor light elements is altered.

18. A kit for transporting individual pieces of a ready-to-assemble illumination system adapted for lighting a subject for film, photography or video, the kit comprising:

a portable light panel having a substantially flat forward-facing mounting surface, said light panel having a plurality of semiconductor light elements secured to said mounting surface so as to provide continuous illumination over an area, said light panel comprising a securing mechanism securable to a camera apparatus whereby the light panel is readily attachable to and detachable from a camera apparatus;

40

a self-contained battery unit comprising a battery housing securably and rigidly attachable to and readily detachable from said portable light panel, such that power from the self-contained battery unit is provided to said semiconductor light elements;

a standalone base plate providing a stable platform for supporting the portable light panel on a level surface; and

a portable case for holding said portable light panel, said self-contained battery unit, and said base plate for transport;

wherein said portable light panel comprises a baseplate attachment member whereby the portable light panel is readily attachable to and detachable from said standalone base plate when said light panel is not mounted to a camera apparatus.

19. The kit of claim 18, wherein said standalone base plate comprises a platform for resting on a flat surface, and a pair of mounting arms on opposite sides of the platform for supportively attaching to the baseplate attachment member of the portable light panel.

20. The kit of claim 18, wherein the portable light panel is rotatable relative to the mounting arms, thereby allowing the portable light panel to tilt at different angles when mounted on the standalone base plate.

21. An illumination system adapted for lighting a subject for film, photography or video, comprising:

a light panel having a forward-facing front mounting surface and a backside with electrical connectors disposed behind said front mounting surface, said light panel having a plurality of broad spectrum semiconductor light elements outputting light across a spectrum spanning at least 450 to 600 nanometers in wavelength, said broad spectrum semiconductor light elements disposed on said front mounting surface so as to provide continuous forward-projected illumination suitable for image capture in motion picture, film or television, and over an area wider than said light panel, said light panel having a securing mechanism securable to a camera apparatus whereby the light panel is readily attachable to and detachable from atop a camera apparatus; and

a dedicated self-contained battery unit having a housing releasably and securably attachable to the backside of said light panel to form a single integrated structure when the light panel and dedicated self-contained battery unit are securably attached together, said housing encasing a battery, such that power from the dedicated self-contained battery unit is provided to said broad spectrum semiconductor light elements via said electrical connectors and is not provided to the camera apparatus.

22. The illumination system of claim 21, wherein said broad spectrum semiconductor light elements comprise broad spectrum light emitting diodes (LEDs) outputting light across a spectrum spanning at least 450 to 600 nanometers in wavelength.

23. The illumination system of claim 22, wherein said broad spectrum LEDs span a white color temperature range and/or a tungsten color temperature range.

* * * * *